

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	12 Hour 19 Min 28 Sec
Total Counter :	29244	Total Running Time :	1024 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.09	kN	No		
HEP :	25.0 %	17.40	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.20	kN	Yes 10	Times	
Ref :		13.92	kN			
LCP :	2.0 %	13.64	kN	Yes 10	Times	
LEP :	25.0 %	10.44	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.74	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.34	kN	Min :	4.24	kN	Punch NO.;	19
SD :	1.00	%	Max :	4.44	kN	Punch NO.;	53
Mean Main Pressure :	13.84	kN	Min :	13.12	kN	Punch NO.;	19
SD :	2.10	%	Max :	14.55	kN	Punch NO.;	35
Filling Depth :	Increase ; 2	Times	Decrease ; 3	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	7.73	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	19
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	61
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	29244	Tablets			
A.W.C Counter :	24531	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	24528 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	rp98927	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	12 Hour 19 Min 28 Sec
Total Counter :	29244	Total Running Time :	1024 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.03	kN	No		
HEP :	25.0 %	18.30	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.93	kN	Yes 10	Times	
Ref :		14.64	kN			
LCP :	2.0 %	14.35	kN	Yes 10	Times	
LEP :	25.0 %	10.98	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.41	kN	Min :	4.27	kN	Punch NO.;	32
SD :	1.40	%	Max :	4.60	kN	Punch NO.;	76
Mean Main Pressure :	14.43	kN	Min :	13.54	kN	Punch NO.;	37
SD :	3.40	%	Max :	16.28	kN	Punch NO.;	76
Filling Depth :	Increase ; 8	Times	Decrease ; 1	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	2.10	mm
Filling Depth :	7.61	mm	Current Cam :	Cam C	
Main Air pressure :	0.768	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	19
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.19	kN	Max Punch ;	61
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	29244	Tablets			
A.W.C Counter :	24531	Tablets			
HEP :	3 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	24528 (100.0%)	Tablets			