

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pb97604	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	19 Hour 56 Min 28 Sec
Total Counter :	2001578	Total Running Time :	1032 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.39	kN	No		
HEP :	25.0 %	22.49	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.35	kN	Yes 10	Times	
Ref :		17.99	kN			
LCP :	2.0 %	17.63	kN	Yes 10	Times	
LEP :	25.0 %	13.49	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.59	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.43	kN	Min :	4.29	kN	Punch NO.;	28
SD :	1.10	%	Max :	4.59	kN	Punch NO.;	76
Mean Main Pressure :	18.03	kN	Min :	16.59	kN	Punch NO.;	28
SD :	2.70	%	Max :	19.66	kN	Punch NO.;	76
Filling Depth :	Increase ; 49	Times	Decrease ;	106	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.95	mm
Filling Depth :	8.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.31	kN	Max Punch ;	6
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	2001578	Tablets			
A.W.C Counter :	1996680	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1996667 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pb97604	Batch NO. :	SHM2501210
Print Interval :	50000 Tablets	Running Time :	19 Hour 56 Min 28 Sec
Total Counter :	2001578	Total Running Time :	1032 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.51	kN	No		
HEP :	25.0 %	22.60	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	18.44	kN	Yes 10	Times	
Ref :		18.08	kN			
LCP :	2.0 %	17.72	kN	Yes 10	Times	
LEP :	25.0 %	13.56	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	12.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.30	kN	Min :	4.16	kN	Punch NO.;	16
SD :	1.40	%	Max :	4.50	kN	Punch NO.;	30
Mean Main Pressure :	18.11	kN	Min :	16.92	kN	Punch NO.;	16
SD :	3.70	%	Max :	20.22	kN	Punch NO.;	35
Filling Depth :	Increase ; 188	Times	Decrease ;	196	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	2.05	mm
Filling Depth :	7.94	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.23	kN		
	Max ;	0.31	kN	Max Punch ;	6
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	36
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	2001578	Tablets			
A.W.C Counter :	1996680	Tablets			
HEP :	13 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1996667 (100.0%)	Tablets			