

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	11 Hour 29 Min 24 Sec
Total Counter :	2978642	Total Running Time :	1047 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.45	kN	No		
HEP :	25.0 %	20.63	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	16.83	kN	Yes 10	Times	
Ref :		16.50	kN			
LCP :	2.0 %	16.17	kN	Yes 10	Times	
LEP :	25.0 %	12.38	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.49	kN	Min :	4.36	kN	Punch NO.;	24
SD :	1.30	%	Max :	4.69	kN	Punch NO.;	35
Mean Main Pressure :	16.06	kN	Min :	14.95	kN	Punch NO.;	45
SD :	3.50	%	Max :	17.72	kN	Punch NO.;	35
Filling Depth :	Increase ; 305	Times	Decrease ;	352	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.53	mm	Main Thickness ;	2.03	mm
Filling Depth :	8.04	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.778	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.31	kN	Max Punch ;	7
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	2978642	Tablets			
A.W.C Counter :	2973630	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	273 (0.0%)	Tablets
GOOD :	2973346 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	pm98770	Batch NO. :	SHM2501310
Print Interval :	50000 Tablets	Running Time :	11 Hour 29 Min 24 Sec
Total Counter :	2978642	Total Running Time :	1047 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.82	kN	No		
HEP :	25.0 %	20.98	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	17.12	kN	Yes 10	Times	
Ref :		16.78	kN			
LCP :	2.0 %	16.45	kN	Yes 10	Times	
LEP :	25.0 %	12.59	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	11.75	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.16	kN	Min :	4.01	kN	Punch NO.;	56
SD :	2.30	%	Max :	4.42	kN	Punch NO.;	9
Mean Main Pressure :	12.26	kN	Min :	10.92	kN	Punch NO.;	22
SD :	7.60	%	Max :	14.93	kN	Punch NO.;	9
Filling Depth :	Increase ;	1305	Times	Decrease ;	1296	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.64	mm	Main Thickness ;	2.14	mm
Filling Depth :	7.90	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.777	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.29	kN	Max Punch ;	13
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.11	kN	Max Punch ;	37
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	1

Tablet Data (N/A)

Total Counter :	2978642	Tablets			
A.W.C Counter :	2973630	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	273 (0.0%)	Tablets
GOOD :	2973346 (100.0%)	Tablets			