

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 44 Sec
Total Counter :	400174	Total Running Time :	1061 Hour 8 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	63	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.95	kN	No		
HEP :	25.0 %	25.91	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.15	kN	Yes	10 Times	
Ref :		20.73	kN			
LCP :	2.0 %	20.32	kN	Yes	10 Times	
LEP :	25.0 %	15.55	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.51	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.64	kN	Min :	4.46	kN	Punch NO.;	36
SD :	2.00	%	Max :	4.91	kN	Punch NO.;	1
Mean Main Pressure :	20.77	kN	Min :	19.42	kN	Punch NO.;	38
SD :	3.00	%	Max :	22.72	kN	Punch NO.;	13
Filling Depth :	Increase ;	14	Times	Decrease ;	28	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.25	kN	Max Punch ;	30
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	6
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	400174	Tablets			
A.W.C Counter :	392889	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	392887 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	02 Hour 14 Min 44 Sec
Total Counter :	400174	Total Running Time :	1061 Hour 8 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.96	kN	No		
HEP :	25.0 %	25.93	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.16	kN	Yes	10 Times	
Ref :		20.74	kN			
LCP :	2.0 %	20.33	kN	Yes	10 Times	
LEP :	25.0 %	15.56	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.85	kN	Min :	4.54	kN	Punch NO.;	33
SD :	2.80	%	Max :	5.24	kN	Punch NO.;	45
Mean Main Pressure :	20.98	kN	Min :	19.88	kN	Punch NO.;	29
SD :	3.40	%	Max :	23.07	kN	Punch NO.;	13
Filling Depth :	Increase ;	37	Times	Decrease ;	25	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.58	mm	Current Cam :	Cam C	
Main Air pressure :	0.785	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.24	kN	Max Punch ;	33
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.12	kN	Max Punch ;	6
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	400174	Tablets			
A.W.C Counter :	392889	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	392887 (100.0%)	Tablets			