

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	08 Hour 54 Min 37 Sec
Total Counter :	1589270	Total Running Time :	1067 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	63	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.81	kN	No		
HEP :	25.0 %	26.74	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.82	kN	Yes 10	Times	
Ref :		21.39	kN			
LCP :	2.0 %	20.96	kN	Yes 10	Times	
LEP :	25.0 %	16.04	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.64	kN	Min :	4.37	kN	Punch NO.;	33
SD :	2.60	%	Max :	4.96	kN	Punch NO.;	45
Mean Main Pressure :	21.49	kN	Min :	20.26	kN	Punch NO.;	29
SD :	3.60	%	Max :	23.79	kN	Punch NO.;	13
Filling Depth :	Increase ; 12	Times	Decrease ;	19	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.24	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.18	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	1589270	Tablets			
A.W.C Counter :	1581760	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1581749 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	08 Hour 54 Min 37 Sec
Total Counter :	1589270	Total Running Time :	1067 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.96	kN	No		
HEP :	25.0 %	25.93	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.16	kN	Yes 10	Times	
Ref :		20.74	kN			
LCP :	2.0 %	20.33	kN	Yes 10	Times	
LEP :	25.0 %	15.56	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	14.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.49	kN	Min :	4.30	kN	Punch NO.;	31
SD :	1.90	%	Max :	4.70	kN	Punch NO.;	52
Mean Main Pressure :	20.75	kN	Min :	19.65	kN	Punch NO.;	46
SD :	3.20	%	Max :	22.48	kN	Punch NO.;	12
Filling Depth :	Increase ;	2	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	7.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.25	kN	Max Punch ;	22
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.18	kN	Max Punch ;	26

Tablet Data (N/A)

Total Counter :	1589270	Tablets			
A.W.C Counter :	1581760	Tablets			
HEP :	11 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1581749 (100.0%)	Tablets			