

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	21 Hour 26 Min 35 Sec
Total Counter :	3826286	Total Running Time :	1080 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.06	kN	No		
HEP :	25.0 %	26.02	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.23	kN	Yes	10 Times	
Ref :		20.81	kN			
LCP :	2.0 %	20.40	kN	Yes	10 Times	
LEP :	25.0 %	15.61	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.70	kN	Min :	4.49	kN	Punch NO.;	26
SD :	1.80	%	Max :	4.86	kN	Punch NO.;	45
Mean Main Pressure :	21.23	kN	Min :	20.09	kN	Punch NO.;	46
SD :	3.10	%	Max :	23.51	kN	Punch NO.;	13
Filling Depth :	Increase ;	50	Times	Decrease ;	42	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.28	kN	Max Punch ;	33
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	3826286	Tablets			
A.W.C Counter :	3814633	Tablets			
HEP :	133 (0.0%)	Tablets	LEP :	382 (0.0%)	Tablets
GOOD :	3814118 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2507750
Print Interval :	50000 Tablets	Running Time :	21 Hour 26 Min 35 Sec
Total Counter :	3826286	Total Running Time :	1080 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.38	kN	No		
HEP :	25.0 %	27.29	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.27	kN	Yes 10	Times	
Ref :		21.83	kN			
LCP :	2.0 %	21.39	kN	Yes 10	Times	
LEP :	25.0 %	16.37	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.28	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.83	kN	Min :	4.60	kN	Punch NO.;	13
SD :	2.10	%	Max :	5.05	kN	Punch NO.;	52
Mean Main Pressure :	21.70	kN	Min :	19.85	kN	Punch NO.;	29
SD :	3.80	%	Max :	24.10	kN	Punch NO.;	13
Filling Depth :	Increase ;	60	Times	Decrease ;	59	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.22	kN		
	Max ;	0.29	kN	Max Punch ;	33
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	31
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	21

Tablet Data (N/A)

Total Counter :	3826286	Tablets			
A.W.C Counter :	3814633	Tablets			
HEP :	133 (0.0%)	Tablets	LEP :	382 (0.0%)	Tablets
GOOD :	3814118 (100.0%)	Tablets			