

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | yd98913       | Batch NO. :          | EWM2507850             |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 24 Min 12 Sec  |
| Total Counter :  | 250068        | Total Running Time : | 1085 Hour 28 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |             |                   |         |                    |              |            |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|------------|
| Feeder :                           | Auto ;      | 50                | %       | Manual ;           | 15           | RPM        |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm    |
| Target Quantity :                  |             | 4500000           | Tablets |                    | Max :        | 12.00 mm   |
| Air Pressure Low Limit :           |             | 0.600             | MPa     |                    |              |            |
| Oil Lubrication :                  |             |                   |         |                    |              |            |
| Upper Punch Interval Time(S1) ;    |             | 60                | Min     | Supply Time ;      | 1.0          | Sec        |
| Lower Punch Interval Time(S2) ;    |             | 10                | Min     | Supply Time ;      | 3.0          | Sec        |
| Powder Supply Time :               |             | 5.0               | Sec     |                    |              |            |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |            |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |            |
| Lower Punch Tightness High Limit : |             | 4.00              | kN      |                    |              |            |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |            |
|                                    |             |                   |         | Stop Condition ;   |              |            |
| HSP :                              | 30.0 %      | 26.33             | kN      | No                 |              |            |
| HEP :                              | 25.0 %      | 25.32             | kN      | Yes                | 10 Rotations | 10 Tablets |
| HCP :                              | 2.0 %       | 20.66             | kN      | Yes                | 10 Times     |            |
| Ref :                              |             | 20.26             | kN      |                    |              |            |
| LCP :                              | 2.0 %       | 19.85             | kN      | Yes                | 10 Times     |            |
| LEP :                              | 25.0 %      | 15.19             | kN      | Yes                | 10 Rotations | 10 Tablets |
| LSP :                              | 30.0 %      | 14.18             | kN      | No                 |              |            |
| SD limit :                         | 35.0 %      |                   |         | Yes                |              |            |
| Pre HSP                            |             | 30.00             | kN      | Yes                |              |            |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations  |
| Empty Punch No. :                  | None        |                   |         |                    |              |            |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 4.71       | kN  | Min : | 4.42       | kN  | Punch NO.; | 36 |
| SD :                 | 2.20       | %   | Max : | 5.07       | kN  | Punch NO.; | 52 |
| Mean Main Pressure : | 20.34      | kN  | Min : | 19.42      | kN  | Punch NO.; | 46 |
| SD :                 | 2.60       | %   | Max : | 21.97      | kN  | Punch NO.; | 12 |
| Filling Depth :      | Increase ; | 137 | Times | Decrease ; | 103 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |                   |              |
|-------------------------------|---------|-----|------------------|-------------------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080            | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14                | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |                   |              |
| Pre Lower Punch Position ;    | 6.35    | mm  | Pre Thickness ;  | 3.36              | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |                   |              |
| Main Lower Punch Position ;   | 5.40    | mm  | Main Thickness ; | 2.41              | mm           |
| Filling Depth :               | 8.09    | mm  | Current Cam :    | Cam C<br>8.5-14mm |              |
| Main Air pressure :           | 0.790   | MPa |                  |                   |              |
| Oil Lubrication status :      |         |     |                  |                   |              |
| Upper Punch Remain Time (S1): | 26      | Min |                  |                   |              |
| Lower Punch Remain Time (S2): | 2       | Min |                  |                   |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |                   |              |
| Powder Status :               | Disable |     | Dust Collector : | Off               |              |
| Initial Reject :              | Off     |     | Buzzer :         | On                |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.17 | kN |             |    |
|                  | Max ;     | 0.23 | kN | Max Punch ; | 30 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 53 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.20 | kN | Max Punch ; | 26 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 250068            | Tablets |       |           |         |
| A.W.C Counter : | 246873            | Tablets |       |           |         |
| HEP :           | 62 (0.0%)         | Tablets | LEP : | 78 (0.0%) | Tablets |
| GOOD :          | 246733<br>(99.9%) | Tablets |       |           |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | yd98913       | Batch NO. :          | EWM2507850             |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 24 Min 12 Sec  |
| Total Counter :  | 250068        | Total Running Time : | 1085 Hour 28 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |             |                   |         |                    |              |            |
|------------------------------------|-------------|-------------------|---------|--------------------|--------------|------------|
| Feeder :                           | Auto ;      | 50                | %       | Manual ;           | 15           | RPM        |
| Filling Cam :                      |             | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm    |
| Target Quantity :                  |             | 4500000           | Tablets |                    | Max :        | 12.00 mm   |
| Air Pressure Low Limit :           |             | 0.600             | MPa     |                    |              |            |
| Oil Lubrication :                  |             |                   |         |                    |              |            |
| Upper Punch Interval Time(S1) ;    |             | 60                | Min     | Supply Time ;      | 1.0          | Sec        |
| Lower Punch Interval Time(S2) ;    |             | 10                | Min     | Supply Time ;      | 3.0          | Sec        |
| Powder Supply Time :               |             | 5.0               | Sec     |                    |              |            |
| Initial Reject Time :              |             | 2                 | Tablets |                    |              |            |
| Upper Punch Tightness High Limit : |             | 1.00              | kN      |                    |              |            |
| Lower Punch Tightness High Limit : |             | 4.00              | kN      |                    |              |            |
| Ejecting Force High Limit :        |             | 4.00              | kN      |                    |              |            |
|                                    |             |                   |         | Stop Condition ;   |              |            |
| HSP :                              | 30.0 %      | 25.91             | kN      | No                 |              |            |
| HEP :                              | 25.0 %      | 24.91             | kN      | Yes                | 10 Rotations | 10 Tablets |
| HCP :                              | 2.0 %       | 20.33             | kN      | Yes                | 10 Times     |            |
| Ref :                              |             | 19.93             | kN      |                    |              |            |
| LCP :                              | 2.0 %       | 19.53             | kN      | Yes                | 10 Times     |            |
| LEP :                              | 25.0 %      | 14.95             | kN      | Yes                | 10 Rotations | 10 Tablets |
| LSP :                              | 30.0 %      | 13.95             | kN      | No                 |              |            |
| SD limit :                         | 35.0 %      |                   |         | Yes                |              |            |
| Pre HSP                            |             | 30.00             | kN      | Yes                |              |            |
| Mean Calculation range :           | 2 Rotations |                   |         | Calculation Pass : | 2            | Rotations  |
| Empty Punch No. :                  | N           |                   |         |                    |              |            |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 4.70       | kN  | Min : | 4.49       | kN  | Punch NO.; | 19 |
| SD :                 | 2.40       | %   | Max : | 4.93       | kN  | Punch NO.; | 53 |
| Mean Main Pressure : | 20.15      | kN  | Min : | 18.83      | kN  | Punch NO.; | 32 |
| SD :                 | 3.30       | %   | Max : | 21.93      | kN  | Punch NO.; | 53 |
| Filling Depth :      | Increase ; | 118 | Times | Decrease ; | 113 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |                   |              |
|-------------------------------|---------|-----|------------------|-------------------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080            | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 14                | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |                   |              |
| Pre Lower Punch Position ;    | 6.30    | mm  | Pre Thickness ;  | 3.31              | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |                   |              |
| Main Lower Punch Position ;   | 5.40    | mm  | Main Thickness ; | 2.41              | mm           |
| Filling Depth :               | 7.79    | mm  | Current Cam :    | Cam C<br>8.5-14mm |              |
| Main Air pressure :           | 0.790   | MPa |                  |                   |              |
| Oil Lubrication status :      |         |     |                  |                   |              |
| Upper Punch Remain Time (S1): | 26      | Min |                  |                   |              |
| Lower Punch Remain Time (S2): | 2       | Min |                  |                   |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |                   |              |
| Powder Status :               | Disable |     | Dust Collector : | Off               |              |
| Initial Reject :              | Off     |     | Buzzer :         | On                |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.17 | kN |             |    |
|                  | Max ;     | 0.22 | kN | Max Punch ; | 19 |
| Lower Punch :    | Average ; | 0.08 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 53 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.20 | kN | Max Punch ; | 26 |

### Tablet Data (N/A)

|                 |                   |         |       |           |         |
|-----------------|-------------------|---------|-------|-----------|---------|
| Total Counter : | 250068            | Tablets |       |           |         |
| A.W.C Counter : | 246873            | Tablets |       |           |         |
| HEP :           | 62 (0.0%)         | Tablets | LEP : | 78 (0.0%) | Tablets |
| GOOD :          | 246733<br>(99.9%) | Tablets |       |           |         |