

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 41 Sec
Total Counter :	500238	Total Running Time :	1086 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.33	kN	No		
HEP :	25.0 %	25.32	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	20.66	kN	Yes	10 Times	
Ref :		20.26	kN			
LCP :	2.0 %	19.85	kN	Yes	10 Times	
LEP :	25.0 %	15.19	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.73	kN	Min :	4.50	kN	Punch NO.;	36
SD :	2.20	%	Max :	4.96	kN	Punch NO.;	43
Mean Main Pressure :	20.50	kN	Min :	19.37	kN	Punch NO.;	46
SD :	2.60	%	Max :	21.74	kN	Punch NO.;	24
Filling Depth :	Increase ;	154	Times	Decrease ;	126	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	8.06	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.23	kN	Max Punch ;	30
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	500238	Tablets			
A.W.C Counter :	496640	Tablets			
HEP :	86 (0.0%)	Tablets	LEP :	152 (0.0%)	Tablets
GOOD :	496402 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2507850
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 41 Sec
Total Counter :	500238	Total Running Time :	1086 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.35	kN	No		
HEP :	25.0 %	25.34	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	20.68	kN	Yes	10	Times
Ref :		20.27	kN			
LCP :	2.0 %	19.87	kN	Yes	10	Times
LEP :	25.0 %	15.20	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.19	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.72	kN	Min :	4.43	kN	Punch NO.;	19
SD :	2.50	%	Max :	4.99	kN	Punch NO.;	1
Mean Main Pressure :	20.22	kN	Min :	18.70	kN	Punch NO.;	46
SD :	3.60	%	Max :	22.17	kN	Punch NO.;	13
Filling Depth :	Increase ;	139	Times	Decrease ;	139	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.04	kN	Max Punch ;	18

Tablet Data (N/A)

Total Counter :	500238	Tablets			
A.W.C Counter :	496640	Tablets			
HEP :	86 (0.0%)	Tablets	LEP :	152 (0.0%)	Tablets
GOOD :	496402 (100.0%)	Tablets			