

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	07 Hour 18 Min 37 Sec
Total Counter :	1023214	Total Running Time :	1116 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.92	kN	No		
HEP :	25.0 %	10.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.57	kN	Yes 15	Times	
Ref :		8.40	kN			
LCP :	2.0 %	8.23	kN	Yes 15	Times	
LEP :	25.0 %	6.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.15	kN	Min :	2.96	kN	Punch NO.;	26
SD :	2.90	%	Max :	3.36	kN	Punch NO.;	36
Mean Main Pressure :	8.44	kN	Min :	7.35	kN	Punch NO.;	3
SD :	6.70	%	Max :	9.54	kN	Punch NO.;	21
Filling Depth :	Increase ; 2	Times	Decrease ;	0	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.44	mm	Pre Thickness ;	3.44	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	7.23	mm	Current Cam :	Cam B	
Main Air pressure :	0.687	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.15	kN	Max Punch ;	15
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1023214	Tablets			
A.W.C Counter :	1010391	Tablets			
HEP :	67 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	1010293 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	07 Hour 18 Min 37 Sec
Total Counter :	1023214	Total Running Time :	1116 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.44	kN	No		
HEP :	25.0 %	10.04	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.19	kN	Yes 15	Times	
Ref :		8.03	kN			
LCP :	2.0 %	7.87	kN	Yes 15	Times	
LEP :	25.0 %	6.02	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.62	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.84	kN	Min :	2.60	kN	Punch NO.;	43
SD :	3.70	%	Max :	3.08	kN	Punch NO.;	53
Mean Main Pressure :	8.02	kN	Min :	7.01	kN	Punch NO.;	3
SD :	5.40	%	Max :	9.11	kN	Punch NO.;	13
Filling Depth :	Increase ; 4	Times	Decrease ; 4	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.42	mm	Pre Thickness ;	3.42	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.45	mm	Current Cam :	Cam B	
Main Air pressure :	0.687	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.15	kN	Max Punch ;	15
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1023214	Tablets			
A.W.C Counter :	1010391	Tablets			
HEP :	67 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	1010293 (100.0%)	Tablets			