

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	10 Hour 10 Min 40 Sec
Total Counter :	1423328	Total Running Time :	1119 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.92	kN	No		
HEP :	25.0 %	10.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.57	kN	Yes 15	Times	
Ref :		8.40	kN			
LCP :	2.0 %	8.23	kN	Yes 15	Times	
LEP :	25.0 %	6.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.88	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.23	kN	Min :	3.05	kN	Punch NO.;	19
SD :	2.80	%	Max :	3.50	kN	Punch NO.;	47
Mean Main Pressure :	8.45	kN	Min :	7.23	kN	Punch NO.;	43
SD :	6.30	%	Max :	9.52	kN	Punch NO.;	49
Filling Depth :	Increase ; 22	Times	Decrease ; 36	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.44	mm	Pre Thickness ;	3.44	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.84	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	26
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1423328	Tablets			
A.W.C Counter :	1409526	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	1409337 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	10 Hour 10 Min 40 Sec
Total Counter :	1423328	Total Running Time :	1119 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	38	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		45	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		18	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.90	kN	No		
HEP :	25.0 %	10.48	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.55	kN	Yes 15	Times	
Ref :		8.39	kN			
LCP :	2.0 %	8.22	kN	Yes 15	Times	
LEP :	25.0 %	6.29	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.25	kN	Min :	3.04	kN	Punch NO.;	13
		3.20	%	Max :	3.49	kN	Punch NO.;	8
Mean Main Pressure :	SD :	8.45	kN	Min :	7.76	kN	Punch NO.;	43
		5.20	%	Max :	9.58	kN	Punch NO.;	39
Filling Depth :	Increase ;	16	Times	Decrease ;	18	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	8	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.751	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	18	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.06	kN	Max Punch ;	26
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1423328	Tablets			
A.W.C Counter :	1409579	Tablets			
HEP :	158 (0.0%)	Tablets	LEP :	31 (0.0%)	Tablets
GOOD :	1409390 (100.0%)	Tablets			