

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 17 Sec
Total Counter :	3798506	Total Running Time :	1136 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.51	kN	No		
HEP :	25.0 %	10.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.25	kN	Yes 15	Times	
Ref :		8.09	kN			
LCP :	2.0 %	7.92	kN	Yes 15	Times	
LEP :	25.0 %	6.07	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.44	kN	Min :	3.17	kN	Punch NO.;	20
SD :	3.40	%	Max :	3.79	kN	Punch NO.;	47
Mean Main Pressure :	8.15	kN	Min :	7.34	kN	Punch NO.;	3
SD :	5.10	%	Max :	9.09	kN	Punch NO.;	21
Filling Depth :	Increase ; 156	Times	Decrease ;	165	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.30	mm	Main Thickness ;	2.30	mm
Filling Depth :	6.83	mm	Current Cam :	Cam B	
Main Air pressure :	0.844	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.23	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.13	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3798506	Tablets			
A.W.C Counter :	3783308	Tablets			
HEP :	598 (0.0%)	Tablets	LEP :	68 (0.0%)	Tablets
GOOD :	3782642 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	03 Hour 38 Min 17 Sec
Total Counter :	3798506	Total Running Time :	1136 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.74	kN	No		
HEP :	25.0 %	10.33	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.43	kN	Yes 15	Times	
Ref :		8.26	kN			
LCP :	2.0 %	8.10	kN	Yes 15	Times	
LEP :	25.0 %	6.20	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.18	kN	Min :	2.95	kN	Punch NO.;	31
SD :	2.90	%	Max :	3.43	kN	Punch NO.;	8
Mean Main Pressure :	8.24	kN	Min :	7.16	kN	Punch NO.;	44
SD :	5.90	%	Max :	9.21	kN	Punch NO.;	21
Filling Depth :	Increase ;	100	Times	Decrease ;	107	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.43	mm	Current Cam :	Cam B	
Main Air pressure :	0.844	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.23	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	3798506	Tablets			
A.W.C Counter :	3783308	Tablets			
HEP :	598 (0.0%)	Tablets	LEP :	68 (0.0%)	Tablets
GOOD :	3782642 (100.0%)	Tablets			