

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	05 Hour 36 Min 23 Sec
Total Counter :	4048584	Total Running Time :	1138 Hour 50 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	45	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.51	kN	No		
HEP :	25.0 %	10.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.25	kN	Yes 15	Times	
Ref :		8.09	kN			
LCP :	2.0 %	7.92	kN	Yes 15	Times	
LEP :	25.0 %	6.07	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.53	kN	Min :	3.33	kN	Punch NO.;	13
SD :	3.20	%	Max :	3.77	kN	Punch NO.;	15
Mean Main Pressure :	8.14	kN	Min :	7.17	kN	Punch NO.;	44
SD :	6.30	%	Max :	9.42	kN	Punch NO.;	21
Filling Depth :	Increase ; 167	Times	Decrease ;	175	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.30	mm	Main Thickness ;	2.30	mm
Filling Depth :	6.86	mm	Current Cam :	Cam B	
Main Air pressure :	0.774	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.22	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	4048584	Tablets			
A.W.C Counter :	4033415	Tablets			
HEP :	653 (0.0%)	Tablets	LEP :	69 (0.0%)	Tablets
GOOD :	4032693 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2507950
Print Interval :	50000 Tablets	Running Time :	05 Hour 36 Min 23 Sec
Total Counter :	4048584	Total Running Time :	1138 Hour 50 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	43	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.82	kN	No		
HEP :	25.0 %	10.40	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.49	kN	Yes	15	Times
Ref :		8.32	kN			
LCP :	2.0 %	8.15	kN	Yes	15	Times
LEP :	25.0 %	6.24	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.21	kN	Min :	3.00	kN	Punch NO.;	32
SD :	2.80	%	Max :	3.37	kN	Punch NO.;	50
Mean Main Pressure :	8.32	kN	Min :	7.37	kN	Punch NO.;	41
SD :	5.60	%	Max :	9.52	kN	Punch NO.;	14
Filling Depth :	Increase ;	114	Times	Decrease ;	124	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.44	mm	Current Cam :	Cam B	
Main Air pressure :	0.774	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	46	Min			
Lower Punch Remain Time (S2):	67	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.22	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	4048584	Tablets			
A.W.C Counter :	4033415	Tablets			
HEP :	653 (0.0%)	Tablets	LEP :	69 (0.0%)	Tablets
GOOD :	4032693 (100.0%)	Tablets			