

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 22 Sec
Total Counter :	200108	Total Running Time :	1143 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.40	kN	No		
HEP :	25.0 %	10.00	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.16	kN	Yes	15	Times
Ref :		8.00	kN			
LCP :	2.0 %	7.84	kN	Yes	15	Times
LEP :	25.0 %	6.00	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.67	kN	Min :	3.41	kN	Punch NO.;	14
		3.80	%	Max :	4.14	kN	Punch NO.;	9
Mean Main Pressure :	SD :	7.98	kN	Min :	6.85	kN	Punch NO.;	44
		6.90	%	Max :	9.27	kN	Punch NO.;	12
Filling Depth :	Increase ;	217	Times	Decrease ;	220	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.30	mm	Main Thickness ;	2.30	mm
Filling Depth :	7.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.830	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	200108	Tablets			
A.W.C Counter :	195439	Tablets			
HEP :	126 (0.1%)	Tablets	LEP :	200 (0.1%)	Tablets
GOOD :	195113 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 22 Sec
Total Counter :	200108	Total Running Time :	1143 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.82	kN	No		
HEP :	25.0 %	10.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.49	kN	Yes 15	Times	
Ref :		8.32	kN			
LCP :	2.0 %	8.15	kN	Yes 15	Times	
LEP :	25.0 %	6.24	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.35	kN	Min :	3.08	kN	Punch NO.;	39
		3.50	%	Max :	3.65	kN	Punch NO.;	5
Mean Main Pressure :		8.30	kN	Min :	7.21	kN	Punch NO.;	43
	SD :	5.50	%	Max :	9.56	kN	Punch NO.;	21
Filling Depth :	Increase ;	145	Times	Decrease ;	153	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	5.35	mm	Pre Thickness ;	3.35	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	4.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.59	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.830	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	43	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.27	kN	Max Punch ;	30
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	200108	Tablets			
A.W.C Counter :	195439	Tablets			
HEP :	126 (0.1%)	Tablets	LEP :	200 (0.1%)	Tablets
GOOD :	195113 (99.8%)	Tablets			