

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	13 Hour 44 Min 40 Sec
Total Counter :	2451154	Total Running Time :	1156 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.52	kN	No		
HEP :	25.0 %	11.08	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.04	kN	Yes 15	Times	
Ref :		8.86	kN			
LCP :	2.0 %	8.69	kN	Yes 15	Times	
LEP :	25.0 %	6.65	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.21	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.19	kN	Min :	3.02	kN	Punch NO.;	14
SD :	2.60	%	Max :	3.44	kN	Punch NO.;	8
Mean Main Pressure :	9.02	kN	Min :	7.98	kN	Punch NO.;	15
SD :	5.40	%	Max :	10.30	kN	Punch NO.;	21
Filling Depth :	Increase ; 327	Times	Decrease ;	368	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	6.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.848	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	2451154	Tablets			
A.W.C Counter :	2445548	Tablets			
HEP :	950 (0.0%)	Tablets	LEP :	619 (0.0%)	Tablets
GOOD :	2443979 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	13 Hour 44 Min 40 Sec
Total Counter :	2451154	Total Running Time :	1156 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.82	kN	No		
HEP :	25.0 %	10.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	8.49	kN	Yes 15	Times	
Ref :		8.32	kN			
LCP :	2.0 %	8.15	kN	Yes 15	Times	
LEP :	25.0 %	6.24	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.01	kN	Min :	2.81	kN	Punch NO.;	33
SD :	3.80	%	Max :	3.31	kN	Punch NO.;	1
Mean Main Pressure :	8.22	kN	Min :	7.42	kN	Punch NO.;	41
SD :	5.10	%	Max :	9.47	kN	Punch NO.;	21
Filling Depth :	Increase ;	214	Times	Decrease ;	209	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.54	mm	Current Cam :	Cam B	
Main Air pressure :	0.848	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	49	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	2451154	Tablets			
A.W.C Counter :	2445548	Tablets			
HEP :	950 (0.0%)	Tablets	LEP :	619 (0.0%)	Tablets
GOOD :	2443979 (99.9%)	Tablets			