

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	00 Hour 41 Min 31 Sec
Total Counter :	4402306	Total Running Time :	1167 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	46	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.52	kN	No		
HEP :	25.0 %	11.07	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.04	kN	Yes 15	Times	
Ref :		8.86	kN			
LCP :	2.0 %	8.68	kN	Yes 15	Times	
LEP :	25.0 %	6.64	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.22	kN	Min :	3.04	kN	Punch NO.;	19
SD :	2.30	%	Max :	3.41	kN	Punch NO.;	8
Mean Main Pressure :	8.84	kN	Min :	8.08	kN	Punch NO.;	15
SD :	5.90	%	Max :	10.40	kN	Punch NO.;	21
Filling Depth :	Increase ; 395	Times	Decrease ;	448	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.27	mm	Main Thickness ;	2.27	mm
Filling Depth :	6.98	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	95	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.21	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	4402306	Tablets			
A.W.C Counter :	4395967	Tablets			
HEP :	1204 (0.0%)	Tablets	LEP :	625 (0.0%)	Tablets
GOOD :	4394138 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508050
Print Interval :	50000 Tablets	Running Time :	00 Hour 41 Min 31 Sec
Total Counter :	4402306	Total Running Time :	1167 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.30	kN	No		
HEP :	25.0 %	10.87	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	8.87	kN	Yes	15	Times
Ref :		8.69	kN			
LCP :	2.0 %	8.52	kN	Yes	15	Times
LEP :	25.0 %	6.52	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.09	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.10	kN	Min :	2.82	kN	Punch NO.;	13
SD :	4.20	%	Max :	3.42	kN	Punch NO.;	8
Mean Main Pressure :	8.50	kN	Min :	7.37	kN	Punch NO.;	43
SD :	6.60	%	Max :	10.08	kN	Punch NO.;	21
Filling Depth :	Increase ;	265	Times	Decrease ;	273	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	6.56	mm	Current Cam :	Cam B	
Main Air pressure :	0.819	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	95	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	4402306	Tablets			
A.W.C Counter :	4395967	Tablets			
HEP :	1204 (0.0%)	Tablets	LEP :	625 (0.0%)	Tablets
GOOD :	4394138 (100.0%)	Tablets			