

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	09 Hour 15 Min 20 Sec
Total Counter :	1650734	Total Running Time :	1176 Hour 48 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.42	kN	No		
HEP :	25.0 %	10.02	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	8.18	kN	Yes	10 Times	
Ref :		8.01	kN			
LCP :	2.0 %	7.85	kN	Yes	10 Times	
LEP :	25.0 %	6.01	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	5.61	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.97	kN	Min :	2.81	kN	Punch NO.;	13
SD :	2.50	%	Max :	3.20	kN	Punch NO.;	8
Mean Main Pressure :	8.16	kN	Min :	7.08	kN	Punch NO.;	3
SD :	5.30	%	Max :	9.12	kN	Punch NO.;	49
Filling Depth :	Increase ;	1034	Times	Decrease ;	1074	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.26	mm
Filling Depth :	7.31	mm	Current Cam :	Cam B	
Main Air pressure :	0.842	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	100	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	1650734	Tablets			
A.W.C Counter :	1643854	Tablets			
HEP :	1150 (0.1%)	Tablets	LEP :	460 (0.0%)	Tablets
GOOD :	1642244 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	09 Hour 15 Min 20 Sec
Total Counter :	1650734	Total Running Time :	1176 Hour 48 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	68	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.24	kN	No		
HEP :	25.0 %	9.85	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	8.04	kN	Yes 10	Times	
Ref :		7.88	kN			
LCP :	2.0 %	7.72	kN	Yes 10	Times	
LEP :	25.0 %	5.91	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	5.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.86	kN	Min :	2.62	kN	Punch NO.;	30
SD :	3.10	%	Max :	3.01	kN	Punch NO.;	8
Mean Main Pressure :	8.04	kN	Min :	7.05	kN	Punch NO.;	26
SD :	6.30	%	Max :	9.36	kN	Punch NO.;	49
Filling Depth :	Increase ;	623	Times	Decrease ;	620	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.39	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.842	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	100	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.22	kN	Max Punch ;	37
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1650734	Tablets			
A.W.C Counter :	1643854	Tablets			
HEP :	1150 (0.1%)	Tablets	LEP :	460 (0.0%)	Tablets
GOOD :	1642244 (99.9%)	Tablets			