

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	19 Hour 37 Min 48 Sec
Total Counter :	3501680	Total Running Time :	1187 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	79	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.59	kN	No		
HEP :	25.0 %	10.19	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	8.31	kN	Yes	10	Times
Ref :		8.15	kN			
LCP :	2.0 %	7.99	kN	Yes	10	Times
LEP :	25.0 %	6.11	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	5.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.96	kN	Min :	2.82	kN	Punch NO.;	30
SD :	2.30	%	Max :	3.15	kN	Punch NO.;	36
Mean Main Pressure :	8.14	kN	Min :	6.87	kN	Punch NO.;	44
SD :	6.80	%	Max :	9.49	kN	Punch NO.;	53
Filling Depth :	Increase ;	1447	Times	Decrease ;	1520	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.47	mm	Pre Thickness ;	3.47	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.26	mm
Filling Depth :	7.28	mm	Current Cam :	Cam B	
Main Air pressure :	0.846	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	90	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.22	kN	Max Punch ;	30
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.20	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	3501680	Tablets			
A.W.C Counter :	3494214	Tablets			
HEP :	1823 (0.1%)	Tablets	LEP :	593 (0.0%)	Tablets
GOOD :	3491798 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2508350
Print Interval :	50000 Tablets	Running Time :	19 Hour 37 Min 48 Sec
Total Counter :	3501680	Total Running Time :	1187 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		100	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.50	kN	No		
HEP :	25.0 %	10.10	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	8.24	kN	Yes 10	Times	
Ref :		8.08	kN			
LCP :	2.0 %	7.92	kN	Yes 10	Times	
LEP :	25.0 %	6.06	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	5.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.92	kN	Min :	2.73	kN	Punch NO.;	32
SD :	2.90	%	Max :	3.18	kN	Punch NO.;	8
Mean Main Pressure :	8.17	kN	Min :	7.18	kN	Punch NO.;	3
SD :	6.00	%	Max :	9.57	kN	Punch NO.;	21
Filling Depth :	Increase ;	888	Times	Decrease ;	890	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.39	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.846	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	49	Min			
Lower Punch Remain Time (S2):	90	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.21	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.20	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	3501680	Tablets			
A.W.C Counter :	3494267	Tablets			
HEP :	1823 (0.1%)	Tablets	LEP :	593 (0.0%)	Tablets
GOOD :	3491851 (99.9%)	Tablets			