

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	07 Hour 46 Min 48 Sec
Total Counter :	1385934	Total Running Time :	1200 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	61	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.99	kN	No		
HEP :	25.0 %	26.91	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	21.96	kN	Yes 10	Times	
Ref :		21.53	kN			
LCP :	2.0 %	21.10	kN	Yes 10	Times	
LEP :	25.0 %	16.15	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.07	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.71	kN	Punch NO.;	20
SD :	1.80	%	Max :	2.97	kN	Punch NO.;	36
Mean Main Pressure :	21.51	kN	Min :	20.05	kN	Punch NO.;	3
SD :	2.70	%	Max :	22.41	kN	Punch NO.;	49
Filling Depth :	Increase ;	71	Times	Decrease ;	77	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.26	mm	Main Thickness ;	2.26	mm
Filling Depth :	7.52	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.825	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	103	Min			
Lower Punch Remain Time (S2):	104	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	31
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1385934	Tablets			
A.W.C Counter :	1379506	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1379496 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	07 Hour 46 Min 48 Sec
Total Counter :	1385934	Total Running Time :	1200 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.55	kN	No		
HEP :	25.0 %	25.53	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	20.83	kN	Yes	10	Times
Ref :		20.43	kN			
LCP :	2.0 %	20.02	kN	Yes	10	Times
LEP :	25.0 %	15.32	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.30	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.86	kN	Min :	2.63	kN	Punch NO.;	43
		3.60	%	Max :	3.11	kN	Punch NO.;	36
Mean Main Pressure :	SD :	20.56	kN	Min :	19.07	kN	Punch NO.;	44
		3.60	%	Max :	22.20	kN	Punch NO.;	21
Filling Depth :	Increase ;	58	Times	Decrease ;	54	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.39	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.18	mm	Current Cam :	Cam C	
Main Air pressure :	0.825	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	103	Min			
Lower Punch Remain Time (S2):	104	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	7
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1385934	Tablets			
A.W.C Counter :	1379506	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1379496 (100.0%)	Tablets			