

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	15 Hour 29 Min 47 Sec
Total Counter :	2652154	Total Running Time :	1208 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.45	kN	No		
HEP :	25.0 %	29.28	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	23.89	kN	Yes	10 Times	
Ref :		23.42	kN			
LCP :	2.0 %	22.95	kN	Yes	10 Times	
LEP :	25.0 %	17.57	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	16.40	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.02	kN	Min :	2.84	kN	Punch NO.;	22
		3.30	%	Max :	3.30	kN	Punch NO.;	38
Mean Main Pressure :	SD :	23.63	kN	Min :	21.80	kN	Punch NO.;	30
		3.70	%	Max :	25.80	kN	Punch NO.;	53
Filling Depth :	Increase ;	120	Times	Decrease ;	75	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	21	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.20	mm	Main Thickness ;	2.20	mm
Filling Depth :	7.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	41
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2652154	Tablets			
A.W.C Counter :	2636441	Tablets			
HEP :	164 (0.0%)	Tablets	LEP :	378 (0.0%)	Tablets
GOOD :	2635899 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	15 Hour 29 Min 47 Sec
Total Counter :	2652154	Total Running Time :	1208 Hour 12 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.16	kN	No		
HEP :	25.0 %	26.12	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.31	kN	Yes	10 Times	
Ref :		20.89	kN			
LCP :	2.0 %	20.48	kN	Yes	10 Times	
LEP :	25.0 %	15.67	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.63	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2 Rotations	
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.73	kN	Min :	2.47	kN	Punch NO.;	17
SD :	4.20	%	Max :	2.99	kN	Punch NO.;	51
Mean Main Pressure :	21.14	kN	Min :	19.14	kN	Punch NO.;	29
SD :	4.00	%	Max :	23.66	kN	Punch NO.;	53
Filling Depth :	Increase ;	69	Times	Decrease ;	70	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.816	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	43
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.16	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2652154	Tablets			
A.W.C Counter :	2636441	Tablets			
HEP :	164 (0.0%)	Tablets	LEP :	378 (0.0%)	Tablets
GOOD :	2635899 (100.0%)	Tablets			