

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	16 Hour 45 Min 30 Sec
Total Counter :	2852204	Total Running Time :	1209 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	97	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.88	kN	No		
HEP :	25.0 %	27.77	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.66	kN	Yes 10	Times	
Ref :		22.21	kN			
LCP :	2.0 %	21.77	kN	Yes 10	Times	
LEP :	25.0 %	16.66	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.55	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.93	kN	Min :	2.78	kN	Punch NO.;	37
SD :	2.60	%	Max :	3.12	kN	Punch NO.;	13
Mean Main Pressure :	22.12	kN	Min :	20.71	kN	Punch NO.;	40
SD :	3.30	%	Max :	24.07	kN	Punch NO.;	51
Filling Depth :	Increase ;	240	Times	Decrease ;	188	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.25	mm	Main Thickness ;	2.25	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.833	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	65	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	41
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2852204	Tablets			
A.W.C Counter :	2836039	Tablets			
HEP :	170 (0.0%)	Tablets	LEP :	378 (0.0%)	Tablets
GOOD :	2835491 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	16 Hour 45 Min 30 Sec
Total Counter :	2852204	Total Running Time :	1209 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.33	kN	No		
HEP :	25.0 %	26.28	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	21.45	kN	Yes	10	Times
Ref :		21.02	kN			
LCP :	2.0 %	20.60	kN	Yes	10	Times
LEP :	25.0 %	15.77	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	14.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.79	kN	Min :	2.56	kN	Punch NO.;	17
SD :	4.30	%	Max :	3.05	kN	Punch NO.;	7
Mean Main Pressure :	20.96	kN	Min :	19.36	kN	Punch NO.;	29
SD :	3.60	%	Max :	22.47	kN	Punch NO.;	13
Filling Depth :	Increase ;	110	Times	Decrease ;	114	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	2.46	mm
Filling Depth :	7.23	mm	Current Cam :	Cam C	
Main Air pressure :	0.833	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	64	Min			
Lower Punch Remain Time (S2):	65	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	43
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	2852204	Tablets			
A.W.C Counter :	2836039	Tablets			
HEP :	170 (0.0%)	Tablets	LEP :	378 (0.0%)	Tablets
GOOD :	2835491 (100.0%)	Tablets			