

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	22 Hour 55 Min 17 Sec
Total Counter :	3904878	Total Running Time :	1215 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.20	kN	No		
HEP :	25.0 %	27.12	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	22.13	kN	Yes	10 Times	
Ref :		21.69	kN			
LCP :	2.0 %	21.26	kN	Yes	10 Times	
LEP :	25.0 %	16.27	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	15.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.89	kN	Min :	2.67	kN	Punch NO.;	14
SD :	4.50	%	Max :	3.51	kN	Punch NO.;	42
Mean Main Pressure :	21.46	kN	Min :	18.76	kN	Punch NO.;	30
SD :	4.80	%	Max :	24.90	kN	Punch NO.;	2
Filling Depth :	Increase ;	157	Times	Decrease ;	122	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.29	mm	Main Thickness ;	2.30	mm
Filling Depth :	7.57	mm	Current Cam :	Cam C	
Main Air pressure :	0.839	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	106	Min			
Lower Punch Remain Time (S2):	107	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.23	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3904878	Tablets			
A.W.C Counter :	3885362	Tablets			
HEP :	333 (0.0%)	Tablets	LEP :	636 (0.0%)	Tablets
GOOD :	3884393 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	vg96371	Batch NO. :	EWM2508950
Print Interval :	50000 Tablets	Running Time :	22 Hour 55 Min 17 Sec
Total Counter :	3904878	Total Running Time :	1215 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.33	kN	No		
HEP :	25.0 %	26.28	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	21.45	kN	Yes	10 Times	
Ref :		21.02	kN			
LCP :	2.0 %	20.60	kN	Yes	10 Times	
LEP :	25.0 %	15.77	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	14.72	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.67	kN	Min :	2.50	kN	Punch NO.;	16
		2.90	%	Max :	2.89	kN	Punch NO.;	48
Mean Main Pressure :	SD :	21.62	kN	Min :	19.30	kN	Punch NO.;	29
		4.20	%	Max :	23.58	kN	Punch NO.;	23
Filling Depth :	Increase ;	66	Times	Decrease ;	67	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.44	mm	Main Thickness ;	2.45	mm
Filling Depth :	7.32	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.839	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	106	Min			
Lower Punch Remain Time (S2):	107	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.24	kN	Max Punch ;	35
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.15	kN	Max Punch ;	27
Ejection Force :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0

Tablet Data (N/A)

Total Counter :	3904878	Tablets			
A.W.C Counter :	3885362	Tablets			
HEP :	333 (0.0%)	Tablets	LEP :	636 (0.0%)	Tablets
GOOD :	3884393 (100.0%)	Tablets			