

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	03 Hour 10 Min 49 Sec
Total Counter :	566526	Total Running Time :	1222 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.44	kN	No		
HEP :	25.0 %	12.92	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	10.54	kN	Yes 10	Times	
Ref :		10.34	kN			
LCP :	2.0 %	10.13	kN	Yes 10	Times	
LEP :	25.0 %	7.75	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	7.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.98	kN	Min :	2.81	kN	Punch NO.;	7
SD :	3.00	%	Max :	3.24	kN	Punch NO.;	42
Mean Main Pressure :	10.19	kN	Min :	8.69	kN	Punch NO.;	29
SD :	5.10	%	Max :	11.31	kN	Punch NO.;	1
Filling Depth :	Increase ; 32	Times	Decrease ; 31	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.17	kN	Max Punch ;	27
Ejection Force :	Average ;	0.34	kN		
	Max ;	0.36	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	566526	Tablets			
A.W.C Counter :	561838	Tablets			
HEP :	327 (0.1%)	Tablets	LEP :	441 (0.1%)	Tablets
GOOD :	561070 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	03 Hour 10 Min 50 Sec
Total Counter :	566574	Total Running Time :	1222 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	1.5	Sec
Lower Punch Interval Time(S2) ;		120	Min	Supply Time ;	1.8	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.74	kN	No		
HEP :	25.0 %	12.25	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	10.00	kN	Yes	10	Times
Ref :		9.80	kN			
LCP :	2.0 %	9.61	kN	Yes	10	Times
LEP :	25.0 %	7.35	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	6.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.82	kN	Min :	2.60	kN	Punch NO.;	27
SD :	3.30	%	Max :	3.03	kN	Punch NO.;	42
Mean Main Pressure :	9.68	kN	Min :	8.19	kN	Punch NO.;	30
SD :	6.00	%	Max :	11.09	kN	Punch NO.;	38
Filling Depth :	Increase ;	22	Times	Decrease ;	12	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	2.49	mm
Filling Depth :	6.79	mm	Current Cam :	Cam B	
Main Air pressure :	0.804	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.24	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.17	kN	Max Punch ;	27
Ejection Force :	Average ;	0.34	kN		
	Max ;	0.36	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	566574	Tablets			
A.W.C Counter :	561891	Tablets			
HEP :	327 (0.1%)	Tablets	LEP :	441 (0.1%)	Tablets
GOOD :	561123 (99.9%)	Tablets			