

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	05 Hour 08 Min 39 Sec
Total Counter :	916664	Total Running Time :	1224 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	71	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.44	kN	No		
HEP :	25.0 %	12.92	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.54	kN	Yes	10 Times	
Ref :		10.34	kN			
LCP :	2.0 %	10.13	kN	Yes	10 Times	
LEP :	25.0 %	7.75	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.90	kN	Min :	2.70	kN	Punch NO.;	7
SD :	3.30	%	Max :	3.16	kN	Punch NO.;	41
Mean Main Pressure :	10.27	kN	Min :	8.55	kN	Punch NO.;	30
SD :	5.60	%	Max :	11.85	kN	Punch NO.;	1
Filling Depth :	Increase ;	167	Times	Decrease ;	163	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.00	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	27
Ejection Force :	Average ;	0.28	kN		
	Max ;	0.43	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	916664	Tablets			
A.W.C Counter :	911790	Tablets			
HEP :	383 (0.0%)	Tablets	LEP :	441 (0.0%)	Tablets
GOOD :	910966 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	am98755	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	05 Hour 08 Min 39 Sec
Total Counter :	916664	Total Running Time :	1224 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	67	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.74	kN	No		
HEP :	25.0 %	12.25	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.00	kN	Yes	10 Times	
Ref :		9.80	kN			
LCP :	2.0 %	9.61	kN	Yes	10 Times	
LEP :	25.0 %	7.35	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	6.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.76	kN	Min :	2.52	kN	Punch NO.;	27
SD :	3.20	%	Max :	2.95	kN	Punch NO.;	43
Mean Main Pressure :	9.87	kN	Min :	8.30	kN	Punch NO.;	29
SD :	6.80	%	Max :	11.61	kN	Punch NO.;	34
Filling Depth :	Increase ;	67	Times	Decrease ;	56	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	2.49	mm
Filling Depth :	6.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.810	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	20	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.20	kN		
	Max ;	0.29	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.14	kN	Max Punch ;	27
Ejection Force :	Average ;	0.28	kN		
	Max ;	0.43	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	916664	Tablets			
A.W.C Counter :	911790	Tablets			
HEP :	383 (0.0%)	Tablets	LEP :	441 (0.0%)	Tablets
GOOD :	910966 (99.9%)	Tablets			