

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	16 Hour 56 Min 00 Sec
Total Counter :	3019154	Total Running Time :	1235 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.28	kN	No		
HEP :	25.0 %	13.73	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	11.20	kN	Yes	10	Times
Ref :		10.98	kN			
LCP :	2.0 %	10.76	kN	Yes	10	Times
LEP :	25.0 %	8.24	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	7.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.17	kN	Min :	2.99	kN	Punch NO.;	27
		3.10	%	Max :	3.35	kN	Punch NO.;	21
Mean Main Pressure :		11.01	kN	Min :	9.80	kN	Punch NO.;	30
	SD :	6.10	%	Max :	12.50	kN	Punch NO.;	35
Filling Depth :	Increase ;	83	Times	Decrease ;	94	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.08	mm	Current Cam :	Cam B	
Main Air pressure :	0.770	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.32	kN	Max Punch ;	41
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	27
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.23	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	3019154	Tablets			
A.W.C Counter :	3010786	Tablets			
HEP :	1056 (0.0%)	Tablets	LEP :	869 (0.0%)	Tablets
GOOD :	3008861 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	16 Hour 56 Min 00 Sec
Total Counter :	3019154	Total Running Time :	1235 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.26	kN	No		
HEP :	25.0 %	12.75	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	10.40	kN	Yes	10 Times	
Ref :		10.20	kN			
LCP :	2.0 %	9.99	kN	Yes	10 Times	
LEP :	25.0 %	7.65	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.14	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.01	kN	Min :	2.80	kN	Punch NO.;	17
SD :	4.50	%	Max :	3.48	kN	Punch NO.;	42
Mean Main Pressure :	10.32	kN	Min :	8.65	kN	Punch NO.;	29
SD :	6.50	%	Max :	11.75	kN	Punch NO.;	53
Filling Depth :	Increase ;	108	Times	Decrease ;	102	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	2.51	mm
Filling Depth :	6.90	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.770	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.21	kN		
	Max ;	0.32	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	27
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.23	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	3019154	Tablets			
A.W.C Counter :	3010786	Tablets			
HEP :	1056 (0.0%)	Tablets	LEP :	869 (0.0%)	Tablets
GOOD :	3008861 (99.9%)	Tablets			