

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	ms88737	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	20 Hour 17 Min 57 Sec
Total Counter :	3619560	Total Running Time :	1239 Hour 13 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.28	kN	No		
HEP :	25.0 %	13.73	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	11.20	kN	Yes 15	Times	
Ref :		10.98	kN			
LCP :	2.0 %	10.76	kN	Yes 15	Times	
LEP :	25.0 %	8.24	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.16	kN	Min :	2.92	kN	Punch NO.;	27
		3.30	%	Max :	3.38	kN	Punch NO.;	43
Mean Main Pressure :		11.12	kN	Min :	9.24	kN	Punch NO.;	30
	SD :	6.50	%	Max :	12.62	kN	Punch NO.;	23
Filling Depth :	Increase ;	319	Times	Decrease ;	305	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.34	mm	Main Thickness ;	2.35	mm
Filling Depth :	7.39	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.27	kN	Max Punch ;	42
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	3619560	Tablets			
A.W.C Counter :	3605367	Tablets			
HEP :	1231 (0.0%)	Tablets	LEP :	999 (0.0%)	Tablets
GOOD :	3603137 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	ms88737	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	20 Hour 17 Min 57 Sec
Total Counter :	3619560	Total Running Time :	1239 Hour 13 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.58	kN	No		
HEP :	25.0 %	13.06	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.65	kN	Yes	15	Times
Ref :		10.45	kN			
LCP :	2.0 %	10.24	kN	Yes	15	Times
LEP :	25.0 %	7.83	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.98	kN	Min :	2.82	kN	Punch NO.;	19
SD :	2.90	%	Max :	3.20	kN	Punch NO.;	42
Mean Main Pressure :	10.36	kN	Min :	8.98	kN	Punch NO.;	40
SD :	6.50	%	Max :	11.66	kN	Punch NO.;	23
Filling Depth :	Increase ;	224	Times	Decrease ;	219	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	2.51	mm
Filling Depth :	6.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.803	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.26	kN	Max Punch ;	41
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	3619560	Tablets			
A.W.C Counter :	3605367	Tablets			
HEP :	1231 (0.0%)	Tablets	LEP :	999 (0.0%)	Tablets
GOOD :	3603137 (99.9%)	Tablets			