

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	00 Hour 06 Min 10 Sec
Total Counter :	4298274	Total Running Time :	1243 Hour 1 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.28	kN	No		
HEP :	25.0 %	13.73	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	11.20	kN	Yes	15	Times
Ref :		10.98	kN			
LCP :	2.0 %	10.76	kN	Yes	15	Times
LEP :	25.0 %	8.24	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.69	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.17	kN	Min :	2.97	kN	Punch NO.;	12
SD :	3.10	%	Max :	3.41	kN	Punch NO.;	43
Mean Main Pressure :	11.00	kN	Min :	9.69	kN	Punch NO.;	30
SD :	5.30	%	Max :	12.32	kN	Punch NO.;	23
Filling Depth :	Increase ;	167	Times	Decrease ;	210	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.823	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.19	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	4298274	Tablets			
A.W.C Counter :	4282853	Tablets			
HEP :	1465 (0.0%)	Tablets	LEP :	1375 (0.0%)	Tablets
GOOD :	4280013 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	yu98249	Batch NO. :	EWM2509450
Print Interval :	50000 Tablets	Running Time :	00 Hour 06 Min 10 Sec
Total Counter :	4298274	Total Running Time :	1243 Hour 1 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.58	kN	No		
HEP :	25.0 %	13.06	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.65	kN	Yes	15	Times
Ref :		10.45	kN			
LCP :	2.0 %	10.24	kN	Yes	15	Times
LEP :	25.0 %	7.83	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.04	kN	Min :	2.86	kN	Punch NO.;	27
		3.00	%	Max :	3.20	kN	Punch NO.;	42
Mean Main Pressure :		10.54	kN	Min :	9.12	kN	Punch NO.;	29
	SD :	5.90	%	Max :	12.02	kN	Punch NO.;	53
Filling Depth :	Increase ;	104	Times	Decrease ;	101	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	7.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.823	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.20	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.11	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.19	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	4298274	Tablets			
A.W.C Counter :	4282853	Tablets			
HEP :	1465 (0.0%)	Tablets	LEP :	1375 (0.0%)	Tablets
GOOD :	4280013 (99.9%)	Tablets			