

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	20 Hour 11 Min 03 Sec
Total Counter :	3602486	Total Running Time :	1264 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.69	kN	No		
HEP :	25.0 %	13.16	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.74	kN	Yes 15	Times	
Ref :		10.53	kN			
LCP :	2.0 %	10.32	kN	Yes 15	Times	
LEP :	25.0 %	7.90	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.37	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.12	kN	Min :	2.89	kN	Punch NO.;	19
SD :	2.90	%	Max :	3.38	kN	Punch NO.;	42
Mean Main Pressure :	10.53	kN	Min :	8.78	kN	Punch NO.;	30
SD :	5.70	%	Max :	11.52	kN	Punch NO.;	39
Filling Depth :	Increase ; 37	Times	Decrease ; 34	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.649	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.16	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	3602486	Tablets			
A.W.C Counter :	3595820	Tablets			
HEP :	725 (0.0%)	Tablets	LEP :	221 (0.0%)	Tablets
GOOD :	3594874 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	20 Hour 11 Min 03 Sec
Total Counter :	3602486	Total Running Time :	1264 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.94	kN	No		
HEP :	25.0 %	12.44	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.15	kN	Yes 15	Times	
Ref :		9.95	kN			
LCP :	2.0 %	9.76	kN	Yes 15	Times	
LEP :	25.0 %	7.47	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.94	kN	Min :	2.73	kN	Punch NO.;	16
SD :	3.10	%	Max :	3.16	kN	Punch NO.;	41
Mean Main Pressure :	9.87	kN	Min :	8.44	kN	Punch NO.;	30
SD :	5.90	%	Max :	11.00	kN	Punch NO.;	53
Filling Depth :	Increase ;	28	Times	Decrease ;	28	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	6.95	mm	Current Cam :	Cam B	
Main Air pressure :	0.649	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	7	Min			
Lower Punch Remain Time (S2):	7	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.10	kN	Max Punch ;	27
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.20	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	3602486	Tablets			
A.W.C Counter :	3595873	Tablets			
HEP :	725 (0.0%)	Tablets	LEP :	221 (0.0%)	Tablets
GOOD :	3594927 (100.0%)	Tablets			