

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	21 Hour 01 Min 30 Sec
Total Counter :	3752578	Total Running Time :	1265 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.69	kN	No		
HEP :	25.0 %	13.16	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.74	kN	Yes	15	Times
Ref :		10.53	kN			
LCP :	2.0 %	10.32	kN	Yes	15	Times
LEP :	25.0 %	7.90	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.37	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.13	kN	Min :	2.96	kN	Punch NO.;	19
SD :	2.80	%	Max :	3.30	kN	Punch NO.;	11
Mean Main Pressure :	10.42	kN	Min :	9.30	kN	Punch NO.;	15
SD :	5.30	%	Max :	11.44	kN	Punch NO.;	38
Filling Depth :	Increase ;	73	Times	Decrease ;	72	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.10	mm	Current Cam :	Cam B	
Main Air pressure :	0.612	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3752578	Tablets			
A.W.C Counter :	3745916	Tablets			
HEP :	757 (0.0%)	Tablets	LEP :	221 (0.0%)	Tablets
GOOD :	3744938 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	21 Hour 01 Min 30 Sec
Total Counter :	3752578	Total Running Time :	1265 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.94	kN	No		
HEP :	25.0 %	12.44	kN	Yes	10 Rotations	15 Tablets
HCP :	2.0 %	10.15	kN	Yes	15 Times	
Ref :		9.95	kN			
LCP :	2.0 %	9.76	kN	Yes	15 Times	
LEP :	25.0 %	7.47	kN	Yes	10 Rotations	15 Tablets
LSP :	30.0 %	6.97	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2 Rotations	
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.97	kN	Min :	2.77	kN	Punch NO.;	27
SD :	3.10	%	Max :	3.26	kN	Punch NO.;	46
Mean Main Pressure :	10.00	kN	Min :	8.88	kN	Punch NO.;	29
SD :	6.20	%	Max :	11.31	kN	Punch NO.;	6
Filling Depth :	Increase ;	46	Times	Decrease ;	47	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	6.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.612	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	17	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	27
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.20	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	3752578	Tablets			
A.W.C Counter :	3745916	Tablets			
HEP :	757 (0.0%)	Tablets	LEP :	221 (0.0%)	Tablets
GOOD :	3744938 (100.0%)	Tablets			