

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	00 Hour 56 Min 55 Sec
Total Counter :	4453008	Total Running Time :	1269 Hour 2 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	15	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.64	kN	No		
HEP :	25.0 %	13.11	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	10.70	kN	Yes 15	Times	
Ref :		10.49	kN			
LCP :	2.0 %	10.28	kN	Yes 15	Times	
LEP :	25.0 %	7.87	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	7.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.07	kN	Min :	2.82	kN	Punch NO.;	1
SD :	3.10	%	Max :	3.32	kN	Punch NO.;	38
Mean Main Pressure :	10.37	kN	Min :	8.70	kN	Punch NO.;	29
SD :	6.40	%	Max :	11.82	kN	Punch NO.;	46
Filling Depth :	Increase ;	224	Times	Decrease ;	213	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.06	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	29
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.17	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	4453008	Tablets			
A.W.C Counter :	4446176	Tablets			
HEP :	924 (0.0%)	Tablets	LEP :	324 (0.0%)	Tablets
GOOD :	4444928 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2509850
Print Interval :	50000 Tablets	Running Time :	00 Hour 56 Min 55 Sec
Total Counter :	4453008	Total Running Time :	1269 Hour 2 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.87	kN	No		
HEP :	25.0 %	12.37	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.10	kN	Yes	15	Times
Ref :		9.90	kN			
LCP :	2.0 %	9.70	kN	Yes	15	Times
LEP :	25.0 %	7.42	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.93	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.96	kN	Min :	2.73	kN	Punch NO.;	14
SD :	4.10	%	Max :	3.23	kN	Punch NO.;	51
Mean Main Pressure :	10.10	kN	Min :	8.30	kN	Punch NO.;	30
SD :	7.00	%	Max :	11.70	kN	Punch NO.;	13
Filling Depth :	Increase ;	174	Times	Decrease ;	176	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	6.85	mm	Current Cam :	Cam B	
Main Air pressure :	0.793	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.18	kN	Max Punch ;	28
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	6
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.13	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	4453008	Tablets			
A.W.C Counter :	4446176	Tablets			
HEP :	924 (0.0%)	Tablets	LEP :	324 (0.0%)	Tablets
GOOD :	4444928 (100.0%)	Tablets			