

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	15 Hour 59 Min 30 Sec
Total Counter :	2851492	Total Running Time :	1285 Hour 15 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.59	kN	No		
HEP :	25.0 %	25.57	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.86	kN	Yes 15	Times	
Ref :		20.45	kN			
LCP :	2.0 %	20.04	kN	Yes 15	Times	
LEP :	25.0 %	15.34	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.32	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.92	kN	Min :	2.71	kN	Punch NO.;	17
SD :	2.80	%	Max :	3.11	kN	Punch NO.;	41
Mean Main Pressure :	20.41	kN	Min :	18.71	kN	Punch NO.;	30
SD :	3.40	%	Max :	21.72	kN	Punch NO.;	34
Filling Depth :	Increase ;	1007	Times	Decrease ;	975	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.46	mm	Pre Thickness ;	3.46	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.33	mm	Main Thickness ;	2.34	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.17	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	29
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.06	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	2851492	Tablets			
A.W.C Counter :	2843136	Tablets			
HEP :	872 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2842263 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pr190041	Batch NO. :	EWM2510050
Print Interval :	50000 Tablets	Running Time :	15 Hour 59 Min 30 Sec
Total Counter :	2851492	Total Running Time :	1285 Hour 15 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	50	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.41	kN	No		
HEP :	25.0 %	25.39	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	20.72	kN	Yes	15	Times
Ref :		20.31	kN			
LCP :	2.0 %	19.91	kN	Yes	15	Times
LEP :	25.0 %	15.23	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	14.22	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.79	kN	Min :	2.56	kN	Punch NO.;	27
SD :	3.20	%	Max :	2.93	kN	Punch NO.;	11
Mean Main Pressure :	20.31	kN	Min :	18.52	kN	Punch NO.;	29
SD :	3.40	%	Max :	21.74	kN	Punch NO.;	13
Filling Depth :	Increase ;	432	Times	Decrease ;	432	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.41	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.49	mm	Main Thickness ;	2.50	mm
Filling Depth :	7.59	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.17	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.09	kN	Max Punch ;	4
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.11	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	2851492	Tablets			
A.W.C Counter :	2843136	Tablets			
HEP :	872 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2842263 (100.0%)	Tablets			