

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	00 Hour 37 Min 31 Sec
Total Counter :	85346	Total Running Time :	1295 Hour 3 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.29	kN	No		
HEP :	25.0 %	29.12	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.76	kN	Yes 15	Times	
Ref :		23.30	kN			
LCP :	2.0 %	22.83	kN	Yes 15	Times	
LEP :	25.0 %	17.47	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.30	kN	Min :	3.05	kN	Punch NO.;	35
		3.50	%	Max :	3.64	kN	Punch NO.;	45
Mean Main Pressure :	SD :	23.57	kN	Min :	22.02	kN	Punch NO.;	35
		2.90	%	Max :	25.62	kN	Punch NO.;	45
Filling Depth :	Increase ;	48	Times	Decrease ;	40	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	2.35	mm
Filling Depth :	8.22	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	1
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.06	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	85346	Tablets			
A.W.C Counter :	79677	Tablets			
HEP :	90 (0.1%)	Tablets	LEP :	226 (0.3%)	Tablets
GOOD :	79361 (99.6%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pm98770	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	00 Hour 37 Min 31 Sec
Total Counter :	85346	Total Running Time :	1295 Hour 3 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	65	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.01	kN	No		
HEP :	25.0 %	29.82	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	24.33	kN	Yes	15	Times
Ref :		23.85	kN			
LCP :	2.0 %	23.38	kN	Yes	15	Times
LEP :	25.0 %	17.89	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	16.70	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.66	kN	Min :	2.31	kN	Punch NO.;	49
		5.40	%	Max :	2.95	kN	Punch NO.;	3
Mean Main Pressure :	SD :	23.84	kN	Min :	21.38	kN	Punch NO.;	49
		4.00	%	Max :	25.65	kN	Punch NO.;	3
Filling Depth :	Increase ;	36	Times	Decrease ;	50	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	13	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	6.40	mm	Pre Thickness ;	3.40	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.806	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	41
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.05	kN	Max Punch ;	10

Tablet Data (N/A)

Total Counter :	85346	Tablets			
A.W.C Counter :	79677	Tablets			
HEP :	90 (0.1%)	Tablets	LEP :	226 (0.3%)	Tablets
GOOD :	79361 (99.6%)	Tablets			