

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	12 Hour 25 Min 34 Sec
Total Counter :	1795172	Total Running Time :	1306 Hour 51 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	85	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.18	kN	No		
HEP :	25.0 %	28.06	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.90	kN	Yes 15	Times	
Ref :		22.45	kN			
LCP :	2.0 %	22.00	kN	Yes 15	Times	
LEP :	25.0 %	16.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.71	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.26	kN	Min :	3.05	kN	Punch NO.;	35
		3.20	%	Max :	3.52	kN	Punch NO.;	5
Mean Main Pressure :	SD :	22.32	kN	Min :	20.92	kN	Punch NO.;	35
		3.00	%	Max :	23.70	kN	Punch NO.;	40
Filling Depth :	Increase ;	75	Times	Decrease ;	64	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	152640	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	2.36	mm
Filling Depth :	8.10	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	1795172	Tablets			
A.W.C Counter :	1787144	Tablets			
HEP :	502 (0.0%)	Tablets	LEP :	840 (0.0%)	Tablets
GOOD :	1785802 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2510250
Print Interval :	50000 Tablets	Running Time :	12 Hour 25 Min 34 Sec
Total Counter :	1795172	Total Running Time :	1306 Hour 51 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		10.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.73	kN	No		
HEP :	25.0 %	27.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.54	kN	Yes	15	Times
Ref :		22.10	kN			
LCP :	2.0 %	21.66	kN	Yes	15	Times
LEP :	25.0 %	16.58	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.47	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.80	kN	Min :	2.54	kN	Punch NO.;	37
SD :	4.20	%	Max :	3.15	kN	Punch NO.;	40
Mean Main Pressure :	21.72	kN	Min :	19.87	kN	Punch NO.;	37
SD :	4.40	%	Max :	24.57	kN	Punch NO.;	40
Filling Depth :	Increase ;	81	Times	Decrease ;	81	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	24	RPM	Capacity :	152640	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.40	mm
Filling Depth :	7.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.824	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	5
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.09	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	1795172	Tablets			
A.W.C Counter :	1787144	Tablets			
HEP :	502 (0.0%)	Tablets	LEP :	840 (0.0%)	Tablets
GOOD :	1785802 (99.9%)	Tablets			