

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2510750
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 50 Sec
Total Counter :	50034	Total Running Time :	1375 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.18	kN	No		
HEP :	25.0 %	29.02	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.68	kN	Yes 15	Times	
Ref :		23.22	kN			
LCP :	2.0 %	22.75	kN	Yes 15	Times	
LEP :	25.0 %	17.41	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.51	kN	Min :	3.26	kN	Punch NO.;	46
SD :	3.10	%	Max :	3.78	kN	Punch NO.;	3
Mean Main Pressure :	22.96	kN	Min :	20.93	kN	Punch NO.;	46
SD :	3.00	%	Max :	24.54	kN	Punch NO.;	3
Filling Depth :	Increase ;	1438	Times	Decrease ;	1456	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.72	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.731	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	50034	Tablets			
A.W.C Counter :	47007	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	47007 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2510750
Print Interval :	50000 Tablets	Running Time :	00 Hour 16 Min 50 Sec
Total Counter :	50034	Total Running Time :	1375 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.30	kN	No		
HEP :	25.0 %	28.18	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.99	kN	Yes	15	Times
Ref :		22.54	kN			
LCP :	2.0 %	22.09	kN	Yes	15	Times
LEP :	25.0 %	16.91	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.78	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.21	kN	Min :	3.00	kN	Punch NO.;	35
		3.90	%	Max :	3.58	kN	Punch NO.;	3
Mean Main Pressure :		22.75	kN	Min :	21.29	kN	Punch NO.;	35
	SD :	3.80	%	Max :	24.85	kN	Punch NO.;	40
Filling Depth :	Increase ;	890	Times	Decrease ;	954	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	7.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.731	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	25	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	On	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	45
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	50034	Tablets			
A.W.C Counter :	47007	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	47007 (100.0%)	Tablets			