

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510750
Print Interval :	50000 Tablets	Running Time :	14 Hour 51 Min 29 Sec
Total Counter :	2651440	Total Running Time :	1389 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	108	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.80	kN	No		
HEP :	25.0 %	28.65	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.38	kN	Yes 15	Times	
Ref :		22.92	kN			
LCP :	2.0 %	22.46	kN	Yes 15	Times	
LEP :	25.0 %	17.19	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.04	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.41	kN	Min :	3.21	kN	Punch NO.;	35
SD :	3.10	%	Max :	3.71	kN	Punch NO.;	26
Mean Main Pressure :	22.82	kN	Min :	21.35	kN	Punch NO.;	35
SD :	3.30	%	Max :	24.56	kN	Punch NO.;	26
Filling Depth :	Increase ;	1903	Times	Decrease ;	1876	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.67	mm	Current Cam :	Cam C	
Main Air pressure :	0.713	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.16	kN	Max Punch ;	39

Tablet Data (N/A)

Total Counter :	2651440	Tablets			
A.W.C Counter :	2645512	Tablets			
HEP :	171 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2645340 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2510750
Print Interval :	50000 Tablets	Running Time :	14 Hour 51 Min 29 Sec
Total Counter :	2651440	Total Running Time :	1389 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	108	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	1.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.73	kN	No		
HEP :	25.0 %	27.63	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.54	kN	Yes	15	Times
Ref :		22.10	kN			
LCP :	2.0 %	21.66	kN	Yes	15	Times
LEP :	25.0 %	16.58	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.47	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.10	kN	Min :	2.90	kN	Punch NO.;	15
SD :	3.40	%	Max :	3.32	kN	Punch NO.;	3
Mean Main Pressure :	22.63	kN	Min :	20.84	kN	Punch NO.;	15
SD :	3.90	%	Max :	24.46	kN	Punch NO.;	45
Filling Depth :	Increase ;	1033	Times	Decrease ;	1097	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.46	mm
Filling Depth :	7.48	mm	Current Cam :	Cam C	
Main Air pressure :	0.713	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.16	kN	Max Punch ;	39

Tablet Data (N/A)

Total Counter :	2651440	Tablets			
A.W.C Counter :	2645512	Tablets			
HEP :	171 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2645340 (100.0%)	Tablets			