

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511050
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 29 Sec
Total Counter :	1050488	Total Running Time :	1406 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	126	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.09	kN	No		
HEP :	25.0 %	27.01	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.04	kN	Yes	15	Times
Ref :		21.61	kN			
LCP :	2.0 %	21.18	kN	Yes	15	Times
LEP :	25.0 %	16.21	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.37	kN	Min :	3.19	kN	Punch NO.;	16
		3.10	%	Max :	3.69	kN	Punch NO.;	25
Mean Main Pressure :	SD :	21.67	kN	Min :	20.58	kN	Punch NO.;	16
		2.80	%	Max :	23.23	kN	Punch NO.;	25
Filling Depth :	Increase ;	114	Times	Decrease ;	137	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	36
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.17	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	1050488	Tablets			
A.W.C Counter :	1039279	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1039279 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511050
Print Interval :	50000 Tablets	Running Time :	05 Hour 53 Min 29 Sec
Total Counter :	1050488	Total Running Time :	1406 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	5.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.77	kN	No		
HEP :	25.0 %	25.74	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	21.01	kN	Yes	15	Times
Ref :		20.59	kN			
LCP :	2.0 %	20.18	kN	Yes	15	Times
LEP :	25.0 %	15.45	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	14.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.09	kN	Min :	2.77	kN	Punch NO.;	52
SD :	4.50	%	Max :	3.39	kN	Punch NO.;	7
Mean Main Pressure :	20.76	kN	Min :	19.02	kN	Punch NO.;	47
SD :	3.90	%	Max :	22.57	kN	Punch NO.;	7
Filling Depth :	Increase ;	34	Times	Decrease ;	42	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.27	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.10	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.19	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	1050488	Tablets			
A.W.C Counter :	1039279	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1039279 (100.0%)	Tablets			