

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511050
Print Interval :	50000 Tablets	Running Time :	11 Hour 30 Min 09 Sec
Total Counter :	2050976	Total Running Time :	1411 Hour 43 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	126	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.91	kN	No		
HEP :	25.0 %	27.80	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.68	kN	Yes 15	Times	
Ref :		22.24	kN			
LCP :	2.0 %	21.79	kN	Yes 15	Times	
LEP :	25.0 %	16.68	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.60	kN	Min :	3.37	kN	Punch NO.;	47
SD :	2.70	%	Max :	3.82	kN	Punch NO.;	50
Mean Main Pressure :	22.92	kN	Min :	21.36	kN	Punch NO.;	22
SD :	2.90	%	Max :	24.69	kN	Punch NO.;	50
Filling Depth :	Increase ;	317	Times	Decrease ;	328	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	35	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	8.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	2050976	Tablets			
A.W.C Counter :	2039215	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2039209 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511050
Print Interval :	50000 Tablets	Running Time :	11 Hour 30 Min 09 Sec
Total Counter :	2050976	Total Running Time :	1411 Hour 43 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	106	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.36	kN	No		
HEP :	25.0 %	26.31	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.47	kN	Yes 15	Times	
Ref :		21.05	kN			
LCP :	2.0 %	20.62	kN	Yes 15	Times	
LEP :	25.0 %	15.78	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.73	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.01	kN	Min :	2.77	kN	Punch NO.;	48
		3.90	%	Max :	3.23	kN	Punch NO.;	7
Mean Main Pressure :	SD :	21.05	kN	Min :	19.35	kN	Punch NO.;	23
		3.90	%	Max :	22.51	kN	Punch NO.;	8
Filling Depth :	Increase ;	98	Times	Decrease ;	107	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.24	mm	Current Cam :	Cam C	
Main Air pressure :	0.803	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	41	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	21
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	2050976	Tablets			
A.W.C Counter :	2039215	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	2039209 (100.0%)	Tablets			