

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511150             |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 41 Min 01 Sec  |
| Total Counter :  | 300232        | Total Running Time : | 1427 Hour 7 Min        |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 126               | %       | Manual ;           | 15           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.600             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40                | Min     | Supply Time ;      | 3.0          | Sec       |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 29.85             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 28.71             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 23.42             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 22.96             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 22.50             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 17.22             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 16.07             | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | None   |                   |         |                    |              |           |

### Pressure Data

|                      |            |       |       |            |       |       |            |    |
|----------------------|------------|-------|-------|------------|-------|-------|------------|----|
| Mean Pre Pressure :  | SD :       | 3.64  | kN    | Min :      | 3.38  | kN    | Punch NO.; | 47 |
|                      |            | 2.50  | %     | Max :      | 3.83  | kN    | Punch NO.; | 37 |
| Mean Main Pressure : |            | 22.88 | kN    | Min :      | 21.42 | kN    | Punch NO.; | 47 |
|                      | SD :       | 2.30  | %     | Max :      | 23.98 | kN    | Punch NO.; | 50 |
| Filling Depth :      | Increase ; | 610   | Times | Decrease ; | 648   | Times |            |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 35       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.32   | mm  | Pre Thickness ;  | 3.33     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.38   | mm  | Main Thickness ; | 2.39     | mm           |
| Filling Depth :               | 7.90   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.822  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 41     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 24     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 9  |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.17 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                    |         |       |        |         |
|-----------------|--------------------|---------|-------|--------|---------|
| Total Counter : | 300232             | Tablets |       |        |         |
| A.W.C Counter : | 297468             | Tablets |       |        |         |
| HEP :           | 6 (0.0%)           | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 297462<br>(100.0%) | Tablets |       |        |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511150             |
| Print Interval : | 50000 Tablets | Running Time :       | 01 Hour 41 Min 01 Sec  |
| Total Counter :  | 300232        | Total Running Time : | 1427 Hour 7 Min        |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 106               | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.600             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 60                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 40                | Min     | Supply Time ;      | 3.0          | Sec       |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 27.83             | kN      | No                 |              |           |
| HEP :                              | 25.0 % | 26.76             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 2.0 %  | 21.84             | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 21.41             | kN      |                    |              |           |
| LCP :                              | 2.0 %  | 20.98             | kN      | Yes 15             | Times        |           |
| LEP :                              | 25.0 % | 16.06             | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 14.99             | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 2            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 3.19       | kN  | Min : | 2.93       | kN  | Punch NO.; | 48 |
| SD :                 | 3.10       | %   | Max : | 3.38       | kN  | Punch NO.; | 40 |
| Mean Main Pressure : | 21.62      | kN  | Min : | 19.84      | kN  | Punch NO.; | 48 |
| SD :                 | 3.10       | %   | Max : | 22.74      | kN  | Punch NO.; | 40 |
| Filling Depth :      | Increase ; | 370 | Times | Decrease ; | 383 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |        |     |                  |          |              |
|-------------------------------|--------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28     | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto   |     | Speed ;          | 30       | RPM          |
| Pre Upper Punch Position ;    | 2.99   | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 6.32   | mm  | Pre Thickness ;  | 3.33     | mm           |
| Main Upper Punch Position ;   | 2.99   | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.46   | mm  | Main Thickness ; | 2.47     | mm           |
| Filling Depth :               | 7.32   | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.822  | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |        |     |                  |          |              |
| Upper Punch Remain Time (S1): | 41     | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 24     | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0      | Min |                  |          |              |
| Powder Status :               | Enable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off    |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.00 | kN |             |    |
|                  | Max ;     | 0.00 | kN | Max Punch ; | 0  |
| Lower Punch :    | Average ; | 0.09 | kN |             |    |
|                  | Max ;     | 0.11 | kN | Max Punch ; | 9  |
| Ejection Force : | Average ; | 0.03 | kN |             |    |
|                  | Max ;     | 0.19 | kN | Max Punch ; | 12 |

### Tablet Data (N/A)

|                 |                    |         |       |        |         |
|-----------------|--------------------|---------|-------|--------|---------|
| Total Counter : | 300232             | Tablets |       |        |         |
| A.W.C Counter : | 297468             | Tablets |       |        |         |
| HEP :           | 6 (0.0%)           | Tablets | LEP : | 0 (0%) | Tablets |
| GOOD :          | 297462<br>(100.0%) | Tablets |       |        |         |