

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511150
Print Interval :	50000 Tablets	Running Time :	11 Hour 13 Min 03 Sec
Total Counter :	2001086	Total Running Time :	1436 Hour 40 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	127	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.47	kN	No		
HEP :	25.0 %	28.33	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.12	kN	Yes 15	Times	
Ref :		22.67	kN			
LCP :	2.0 %	22.21	kN	Yes 15	Times	
LEP :	25.0 %	17.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.50	kN	Min :	3.25	kN	Punch NO.;	35
SD :	2.60	%	Max :	3.73	kN	Punch NO.;	7
Mean Main Pressure :	22.58	kN	Min :	20.82	kN	Punch NO.;	22
SD :	2.60	%	Max :	23.87	kN	Punch NO.;	45
Filling Depth :	Increase ;	758	Times	Decrease ;	776	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	36	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	8.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	19
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	14

Tablet Data (N/A)

Total Counter :	2001086	Tablets			
A.W.C Counter :	1997609	Tablets			
HEP :	173 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1997436 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511150
Print Interval :	50000 Tablets	Running Time :	11 Hour 13 Min 03 Sec
Total Counter :	2001086	Total Running Time :	1436 Hour 40 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	121	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.57	kN	No		
HEP :	25.0 %	27.47	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.42	kN	Yes 15	Times	
Ref :		21.98	kN			
LCP :	2.0 %	21.54	kN	Yes 15	Times	
LEP :	25.0 %	16.48	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.39	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.18	kN	Min :	2.93	kN	Punch NO.;	52
SD :	3.80	%	Max :	3.46	kN	Punch NO.;	28
Mean Main Pressure :	22.14	kN	Min :	20.48	kN	Punch NO.;	52
SD :	3.50	%	Max :	23.69	kN	Punch NO.;	45
Filling Depth :	Increase ;	447	Times	Decrease ;	474	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	34	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.42	mm	Current Cam :	Cam C	
Main Air pressure :	0.805	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	24	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	19
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.14	kN	Max Punch ;	53

Tablet Data (N/A)

Total Counter :	2001086	Tablets			
A.W.C Counter :	1997609	Tablets			
HEP :	173 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1997436 (100.0%)	Tablets			