

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 48 Sec
Total Counter :	100046	Total Running Time :	1451 Hour 11 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.22	kN	No		
HEP :	25.0 %	29.06	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	23.71	kN	Yes 15	Times	
Ref :		23.25	kN			
LCP :	2.0 %	22.78	kN	Yes 15	Times	
LEP :	25.0 %	17.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	16.27	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.69	kN	Min :	3.50	kN	Punch NO.;	17
		2.60	%	Max :	3.91	kN	Punch NO.;	7
Mean Main Pressure :	SD :	23.30	kN	Min :	22.03	kN	Punch NO.;	22
		2.70	%	Max :	24.75	kN	Punch NO.;	7
Filling Depth :	Increase ;	66	Times	Decrease ;	65	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	27	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	8.25	mm	Current Cam :	Cam C	
Main Air pressure :	0.774	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.20	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	100046	Tablets			
A.W.C Counter :	95594	Tablets			
HEP :	12 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	95579 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	sj97904	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	00 Hour 33 Min 48 Sec
Total Counter :	100046	Total Running Time :	1451 Hour 11 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.22	kN	No		
HEP :	25.0 %	28.10	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	22.93	kN	Yes 15	Times	
Ref :		22.48	kN			
LCP :	2.0 %	22.03	kN	Yes 15	Times	
LEP :	25.0 %	16.86	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	15.73	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.29	kN	Min :	3.07	kN	Punch NO.;	47
		3.30	%	Max :	3.50	kN	Punch NO.;	50
Mean Main Pressure :	SD :	22.50	kN	Min :	20.91	kN	Punch NO.;	47
		3.30	%	Max :	24.03	kN	Punch NO.;	25
Filling Depth :	Increase ;	35	Times	Decrease ;	38	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.774	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	50	Min			
Lower Punch Remain Time (S2):	33	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.12	kN	Max Punch ;	10
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.20	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	100046	Tablets			
A.W.C Counter :	95594	Tablets			
HEP :	12 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	95579 (100.0%)	Tablets			