

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 23 Sec
Total Counter :	500236	Total Running Time :	1453 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.32	kN	No		
HEP :	25.0 %	28.19	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.01	kN	Yes	15	Times
Ref :		22.55	kN			
LCP :	2.0 %	22.10	kN	Yes	15	Times
LEP :	25.0 %	16.92	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.79	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	3.56	kN	Min :	3.41	kN	Punch NO.;	23
		2.40	%	Max :	3.85	kN	Punch NO.;	45
Mean Main Pressure :		22.72	kN	Min :	21.73	kN	Punch NO.;	35
	SD :	2.50	%	Max :	24.77	kN	Punch NO.;	45
Filling Depth :	Increase ;	111	Times	Decrease ;	117	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.38	mm	Main Thickness ;	2.39	mm
Filling Depth :	7.83	mm	Current Cam :	Cam C	
Main Air pressure :	0.636	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.19	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500236	Tablets			
A.W.C Counter :	495797	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	495775 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511250
Print Interval :	50000 Tablets	Running Time :	02 Hour 48 Min 23 Sec
Total Counter :	500236	Total Running Time :	1453 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	72	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.71	kN	No		
HEP :	25.0 %	26.64	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.74	kN	Yes 15	Times	
Ref :		21.32	kN			
LCP :	2.0 %	20.89	kN	Yes 15	Times	
LEP :	25.0 %	15.99	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.92	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.09	kN	Min :	2.69	kN	Punch NO.;	22
		4.00	%	Max :	3.36	kN	Punch NO.;	45
Mean Main Pressure :	SD :	21.26	kN	Min :	18.65	kN	Punch NO.;	22
		4.00	%	Max :	23.42	kN	Punch NO.;	45
Filling Depth :	Increase ;	73	Times	Decrease ;	73	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	7.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.636	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	38	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	29
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.20	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	500236	Tablets			
A.W.C Counter :	495797	Tablets			
HEP :	18 (0.0%)	Tablets	LEP :	4 (0.0%)	Tablets
GOOD :	495775 (100.0%)	Tablets			