

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 25 Sec
Total Counter :	200124	Total Running Time :	1476 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	94	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.82	kN	No		
HEP :	25.0 %	11.36	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.27	kN	Yes	15	Times
Ref :		9.09	kN			
LCP :	2.0 %	8.91	kN	Yes	15	Times
LEP :	25.0 %	6.82	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.66	kN	Min :	2.35	kN	Punch NO.;	22
SD :	4.60	%	Max :	3.04	kN	Punch NO.;	45
Mean Main Pressure :	9.14	kN	Min :	7.29	kN	Punch NO.;	22
SD :	6.70	%	Max :	10.77	kN	Punch NO.;	45
Filling Depth :	Increase ;	242	Times	Decrease ;	305	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.18	mm	Current Cam :	Cam C	
Main Air pressure :	0.764	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.06	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.14	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	200124	Tablets			
A.W.C Counter :	191686	Tablets			
HEP :	145 (0.1%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	191498 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 25 Sec
Total Counter :	200124	Total Running Time :	1476 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	88	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.78	kN	No		
HEP :	25.0 %	11.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.24	kN	Yes	15	Times
Ref :		9.06	kN			
LCP :	2.0 %	8.88	kN	Yes	15	Times
LEP :	25.0 %	6.79	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.85	kN	Min :	1.57	kN	Punch NO.;	22
SD :	6.60	%	Max :	2.21	kN	Punch NO.;	45
Mean Main Pressure :	9.05	kN	Min :	7.55	kN	Punch NO.;	22
SD :	6.10	%	Max :	10.76	kN	Punch NO.;	45
Filling Depth :	Increase ;	272	Times	Decrease ;	293	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.71	mm	Current Cam :	Cam C	
Main Air pressure :	0.764	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	25	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.09	kN	Max Punch ;	29
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.14	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	200124	Tablets			
A.W.C Counter :	191739	Tablets			
HEP :	145 (0.1%)	Tablets	LEP :	43 (0.0%)	Tablets
GOOD :	191551 (99.9%)	Tablets			