

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	04 Hour 29 Min 24 Sec
Total Counter :	800452	Total Running Time :	1480 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.82	kN	No		
HEP :	25.0 %	11.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.27	kN	Yes 15	Times	
Ref :		9.09	kN			
LCP :	2.0 %	8.91	kN	Yes 15	Times	
LEP :	25.0 %	6.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.62	kN	Min :	2.38	kN	Punch NO.;	1
SD :	4.00	%	Max :	2.94	kN	Punch NO.;	45
Mean Main Pressure :	9.19	kN	Min :	7.93	kN	Punch NO.;	1
SD :	6.10	%	Max :	10.92	kN	Punch NO.;	45
Filling Depth :	Increase ; 384	Times	Decrease ;	442	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.32	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	800452	Tablets			
A.W.C Counter :	792017	Tablets			
HEP :	534 (0.1%)	Tablets	LEP :	98 (0.0%)	Tablets
GOOD :	791385 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	04 Hour 29 Min 24 Sec
Total Counter :	800452	Total Running Time :	1480 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.61	kN	No		
HEP :	25.0 %	11.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.11	kN	Yes 15	Times	
Ref :		8.93	kN			
LCP :	2.0 %	8.76	kN	Yes 15	Times	
LEP :	25.0 %	6.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.45	kN	Punch NO.;	35
SD :	7.30	%	Max :	2.11	kN	Punch NO.;	7
Mean Main Pressure :	9.08	kN	Min :	7.65	kN	Punch NO.;	35
SD :	7.30	%	Max :	10.75	kN	Punch NO.;	7
Filling Depth :	Increase ;	371	Times	Decrease ;	391	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.69	mm	Current Cam :	Cam C	
Main Air pressure :	0.752	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.12	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	23
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.18	kN	Max Punch ;	25

Tablet Data (N/A)

Total Counter :	800452	Tablets			
A.W.C Counter :	792070	Tablets			
HEP :	534 (0.1%)	Tablets	LEP :	98 (0.0%)	Tablets
GOOD :	791438 (99.9%)	Tablets			