

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	10 Hour 06 Min 01 Sec
Total Counter :	1801128	Total Running Time :	1485 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		4500000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.82	kN	No		
HEP :	25.0 %	11.36	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.27	kN	Yes 15	Times	
Ref :		9.09	kN			
LCP :	2.0 %	8.91	kN	Yes 15	Times	
LEP :	25.0 %	6.82	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.36	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.39	kN	Punch NO.;	35
SD :	3.50	%	Max :	2.91	kN	Punch NO.;	45
Mean Main Pressure :	9.05	kN	Min :	7.68	kN	Punch NO.;	35
SD :	5.80	%	Max :	10.77	kN	Punch NO.;	45
Filling Depth :	Increase ;	564	Times	Decrease ;	628	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.41	mm	Main Thickness ;	2.42	mm
Filling Depth :	7.14	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.713	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.14	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	41

Tablet Data (N/A)

Total Counter :	1801128	Tablets			
A.W.C Counter :	1792594	Tablets			
HEP :	1103 (0.1%)	Tablets	LEP :	136 (0.0%)	Tablets
GOOD :	1791355 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511550
Print Interval :	50000 Tablets	Running Time :	10 Hour 06 Min 01 Sec
Total Counter :	1801128	Total Running Time :	1485 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.61	kN	No		
HEP :	25.0 %	11.17	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	9.11	kN	Yes 15	Times	
Ref :		8.93	kN			
LCP :	2.0 %	8.76	kN	Yes 15	Times	
LEP :	25.0 %	6.70	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.25	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.77	kN	Min :	1.57	kN	Punch NO.;	31
SD :	6.30	%	Max :	2.16	kN	Punch NO.;	41
Mean Main Pressure :	8.98	kN	Min :	7.48	kN	Punch NO.;	35
SD :	7.10	%	Max :	11.01	kN	Punch NO.;	41
Filling Depth :	Increase ;	441	Times	Decrease ;	461	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.32	mm	Pre Thickness ;	3.33	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.46	mm	Main Thickness ;	2.47	mm
Filling Depth :	6.69	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.713	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	26	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.14	kN	Max Punch ;	29
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	23
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	35

Tablet Data (N/A)

Total Counter :	1801128	Tablets			
A.W.C Counter :	1792594	Tablets			
HEP :	1103 (0.1%)	Tablets	LEP :	136 (0.0%)	Tablets
GOOD :	1791355 (99.9%)	Tablets			