

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	mr99799	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	01 Hour 41 Min 30 Sec
Total Counter :	300154	Total Running Time :	1502 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	105	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.54	kN	No		
HEP :	25.0 %	25.52	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	20.82	kN	Yes	15	Times
Ref :		20.41	kN			
LCP :	2.0 %	20.01	kN	Yes	15	Times
LEP :	25.0 %	15.31	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	14.29	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.90	kN	Min :	2.84	kN	Punch NO.;	34
SD :	0.80	%	Max :	2.95	kN	Punch NO.;	43
Mean Main Pressure :	20.71	kN	Min :	19.42	kN	Punch NO.;	34
SD :	2.30	%	Max :	21.73	kN	Punch NO.;	43
Filling Depth :	Increase ;	30	Times	Decrease ;	30	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.86	mm	Current Cam :	Cam C	
Main Air pressure :	0.756	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	61	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	43
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	16
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	300154	Tablets			
A.W.C Counter :	294800	Tablets			
HEP :	59 (0.0%)	Tablets	LEP :	291 (0.1%)	Tablets
GOOD :	294450 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	mr99799	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	01 Hour 41 Min 30 Sec
Total Counter :	300154	Total Running Time :	1502 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.69	kN	No		
HEP :	25.0 %	27.59	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	22.51	kN	Yes	15	Times
Ref :		22.07	kN			
LCP :	2.0 %	21.63	kN	Yes	15	Times
LEP :	25.0 %	16.55	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	15.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.66	kN	Min :	2.58	kN	Punch NO.;	34
SD :	1.00	%	Max :	2.71	kN	Punch NO.;	53
Mean Main Pressure :	22.03	kN	Min :	19.81	kN	Punch NO.;	34
SD :	3.00	%	Max :	23.21	kN	Punch NO.;	43
Filling Depth :	Increase ;	37	Times	Decrease ;	43	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.44	mm	Current Cam :	Cam C	
Main Air pressure :	0.756	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	61	Min			
Lower Punch Remain Time (S2):	34	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	43
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	16
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	300154	Tablets			
A.W.C Counter :	294800	Tablets			
HEP :	59 (0.0%)	Tablets	LEP :	291 (0.1%)	Tablets
GOOD :	294450 (99.9%)	Tablets			