

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	05 Hour 03 Min 46 Sec
Total Counter :	900416	Total Running Time :	1505 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	105	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.97	kN	No		
HEP :	25.0 %	25.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	21.16	kN	Yes 15	Times	
Ref :		20.75	kN			
LCP :	2.0 %	20.33	kN	Yes 15	Times	
LEP :	25.0 %	15.56	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.89	kN	Min :	2.85	kN	Punch NO.;	31
SD :	0.80	%	Max :	2.95	kN	Punch NO.;	43
Mean Main Pressure :	21.17	kN	Min :	19.97	kN	Punch NO.;	34
SD :	2.50	%	Max :	22.53	kN	Punch NO.;	43
Filling Depth :	Increase ; 62	Times	Decrease ; 81	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	29	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.91	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	45	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	900416	Tablets			
A.W.C Counter :	894707	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	505 (0.1%)	Tablets
GOOD :	894141 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2512250
Print Interval :	50000 Tablets	Running Time :	05 Hour 03 Min 46 Sec
Total Counter :	900416	Total Running Time :	1505 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.1	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	30.05	kN	No		
HEP :	25.0 %	28.89	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	23.58	kN	Yes	15	Times
Ref :		23.11	kN			
LCP :	2.0 %	22.65	kN	Yes	15	Times
LEP :	25.0 %	17.34	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	16.18	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.63	kN	Min :	2.58	kN	Punch NO.;	41
SD :	1.20	%	Max :	2.71	kN	Punch NO.;	12
Mean Main Pressure :	22.95	kN	Min :	21.13	kN	Punch NO.;	34
SD :	3.10	%	Max :	24.29	kN	Punch NO.;	6
Filling Depth :	Increase ;	54	Times	Decrease ;	72	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.44	mm	Current Cam :	Cam C	
Main Air pressure :	0.759	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	45	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	35
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	12

Tablet Data (N/A)

Total Counter :	900416	Tablets			
A.W.C Counter :	894707	Tablets			
HEP :	61 (0.0%)	Tablets	LEP :	505 (0.1%)	Tablets
GOOD :	894141 (99.9%)	Tablets			