

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511950             |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 20 Min 20 Sec  |
| Total Counter :  | 950598        | Total Running Time : | 1531 Hour 25 Min       |
| Station :        | Station 1     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |       |                      |
|------------------------------------|--------|-------------------|---------|--------------------|-------|----------------------|
| Feeder :                           | Auto ; | 92                | %       | Manual ;           | 15    | RPM                  |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min : | 6.50 mm              |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max : | 12.00 mm             |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |       |                      |
| Oil Lubrication :                  |        |                   |         |                    |       |                      |
| Upper Punch Interval Time(S1) ;    |        | 70                | Min     | Supply Time ;      | 0.2   | Sec                  |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 0.2   | Sec                  |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |       |                      |
| Initial Reject Time :              |        | 1                 | Tablets |                    |       |                      |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |       |                      |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |       |                      |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |       |                      |
|                                    |        |                   |         | Stop Condition ;   |       |                      |
| HSP :                              | 30.0 % | 11.99             | kN      | No                 |       |                      |
| HEP :                              | 25.0 % | 11.53             | kN      | Yes                | 10    | Rotations 15 Tablets |
| HCP :                              | 5.0 %  | 9.68              | kN      | Yes                | 15    | Times                |
| Ref :                              |        | 9.22              | kN      |                    |       |                      |
| LCP :                              | 5.0 %  | 8.76              | kN      | Yes                | 15    | Times                |
| LEP :                              | 25.0 % | 6.92              | kN      | Yes                | 10    | Rotations 15 Tablets |
| LSP :                              | 30.0 % | 6.45              | kN      | No                 |       |                      |
| SD limit :                         | 35.0 % |                   |         | Yes                |       |                      |
| Pre HSP                            |        | 30.00             | kN      | Yes                |       |                      |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 1     | Rotations            |
| Empty Punch No. :                  | None   |                   |         |                    |       |                      |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.77       | kN  | Min : | 2.73       | kN  | Punch NO.; | 26 |
| SD :                 | 0.80       | %   | Max : | 2.83       | kN  | Punch NO.; | 4  |
| Mean Main Pressure : | 9.06       | kN  | Min : | 8.14       | kN  | Punch NO.; | 38 |
| SD :                 | 4.90       | %   | Max : | 10.29      | kN  | Punch NO.; | 11 |
| Filling Depth :      | Increase ; | 549 | Times | Decrease ; | 543 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 26       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.01     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.64    | mm  | Main Thickness ; | 2.65     | mm           |
| Filling Depth :               | 7.30    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.795   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 32      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 45      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.01 | kN |             |    |
|                  | Max ;     | 0.07 | kN | Max Punch ; | 42 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 16 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 24 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 950598            | Tablets |       |            |         |
| A.W.C Counter : | 941656            | Tablets |       |            |         |
| HEP :           | 1390 (0.1%)       | Tablets | LEP : | 949 (0.1%) | Tablets |
| GOOD :          | 939317<br>(99.8%) | Tablets |       |            |         |

## PRODUCTION REPORT

### Product Information

|                  |               |                      |                        |
|------------------|---------------|----------------------|------------------------|
| Machine Name :   | VANTIX P720D  | Product Name :       | MET 500<br>MG,STEW1A00 |
| User ID :        | rp98927       | Batch NO. :          | EWM2511950             |
| Print Interval : | 50000 Tablets | Running Time :       | 05 Hour 20 Min 20 Sec  |
| Total Counter :  | 950598        | Total Running Time : | 1531 Hour 25 Min       |
| Station :        | Station 2     |                      |                        |

### Setting Value

|                                    |        |                   |         |                    |              |           |
|------------------------------------|--------|-------------------|---------|--------------------|--------------|-----------|
| Feeder :                           | Auto ; | 86                | %       | Manual ;           | 20           | RPM       |
| Filling Cam :                      |        | Cam C<br>8.5-14mm |         | Cam Range :        | Min :        | 6.50 mm   |
| Target Quantity :                  |        | 4500000           | Tablets |                    | Max :        | 12.00 mm  |
| Air Pressure Low Limit :           |        | 0.400             | MPa     |                    |              |           |
| Oil Lubrication :                  |        |                   |         |                    |              |           |
| Upper Punch Interval Time(S1) ;    |        | 70                | Min     | Supply Time ;      | 0.2          | Sec       |
| Lower Punch Interval Time(S2) ;    |        | 60                | Min     | Supply Time ;      | 0.2          | Sec       |
| Powder Supply Time :               |        | 30.0              | Sec     |                    |              |           |
| Initial Reject Time :              |        | 1                 | Tablets |                    |              |           |
| Upper Punch Tightness High Limit : |        | 1.00              | kN      |                    |              |           |
| Lower Punch Tightness High Limit : |        | 4.00              | kN      |                    |              |           |
| Ejecting Force High Limit :        |        | 4.00              | kN      |                    |              |           |
|                                    |        |                   |         | Stop Condition ;   |              |           |
| HSP :                              | 30.0 % | 12.33             | kN      | No                 |              |           |
| HEP :                              | 24.0 % | 11.76             | kN      | Yes 10             | Rotations 15 | Tablets   |
| HCP :                              | 5.0 %  | 9.96              | kN      | Yes 15             | Times        |           |
| Ref :                              |        | 9.48              | kN      |                    |              |           |
| LCP :                              | 5.0 %  | 9.01              | kN      | Yes 15             | Times        |           |
| LEP :                              | 24.0 % | 7.21              | kN      | Yes 10             | Rotations 15 | Tablets   |
| LSP :                              | 30.0 % | 6.64              | kN      | No                 |              |           |
| SD limit :                         | 35.0 % |                   |         | Yes                |              |           |
| Pre HSP                            |        | 30.00             | kN      | Yes                |              |           |
| Mean Calculation range :           | 2      | Rotations         |         | Calculation Pass : | 1            | Rotations |
| Empty Punch No. :                  | N      |                   |         |                    |              |           |

### Pressure Data

|                      |            |     |       |            |     |            |    |
|----------------------|------------|-----|-------|------------|-----|------------|----|
| Mean Pre Pressure :  | 2.51       | kN  | Min : | 2.45       | kN  | Punch NO.; | 31 |
| SD :                 | 1.10       | %   | Max : | 2.57       | kN  | Punch NO.; | 6  |
| Mean Main Pressure : | 9.53       | kN  | Min : | 8.42       | kN  | Punch NO.; | 31 |
| SD :                 | 6.90       | %   | Max : | 11.27      | kN  | Punch NO.; | 6  |
| Filling Depth :      | Increase ; | 428 | Times | Decrease ; | 431 | Times      |    |

## PRODUCTION REPORT

### Operation Value

|                               |         |     |                  |          |              |
|-------------------------------|---------|-----|------------------|----------|--------------|
| Disk Speed :                  | 28      | RPM | Capacity :       | 178080   | Tablets/hour |
| Feeder : Status ;             | Auto    |     | Speed ;          | 24       | RPM          |
| Pre Upper Punch Position ;    | 2.99    | mm  |                  |          |              |
| Pre Lower Punch Position ;    | 7.00    | mm  | Pre Thickness ;  | 4.01     | mm           |
| Main Upper Punch Position ;   | 2.99    | mm  |                  |          |              |
| Main Lower Punch Position ;   | 5.60    | mm  | Main Thickness ; | 2.61     | mm           |
| Filling Depth :               | 7.45    | mm  | Current Cam :    | Cam C    |              |
| Main Air pressure :           | 0.795   | MPa |                  | 8.5-14mm |              |
| Oil Lubrication status :      |         |     |                  |          |              |
| Upper Punch Remain Time (S1): | 32      | Min |                  |          |              |
| Lower Punch Remain Time (S2): | 45      | Min |                  |          |              |
| Lower Head Remain Time (S3):  | 0       | Min |                  |          |              |
| Powder Status :               | Disable |     | Dust Collector : | Off      |              |
| Initial Reject :              | Off     |     | Buzzer :         | Off      |              |

### Tightness

|                  |           |      |    |             |    |
|------------------|-----------|------|----|-------------|----|
| Upper Punch :    | Average ; | 0.01 | kN |             |    |
|                  | Max ;     | 0.06 | kN | Max Punch ; | 42 |
| Lower Punch :    | Average ; | 0.13 | kN |             |    |
|                  | Max ;     | 0.15 | kN | Max Punch ; | 16 |
| Ejection Force : | Average ; | 0.04 | kN |             |    |
|                  | Max ;     | 0.16 | kN | Max Punch ; | 24 |

### Tablet Data (N/A)

|                 |                   |         |       |            |         |
|-----------------|-------------------|---------|-------|------------|---------|
| Total Counter : | 950598            | Tablets |       |            |         |
| A.W.C Counter : | 941656            | Tablets |       |            |         |
| HEP :           | 1390 (0.1%)       | Tablets | LEP : | 949 (0.1%) | Tablets |
| GOOD :          | 939317<br>(99.8%) | Tablets |       |            |         |