

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	05 Hour 37 Min 11 Sec
Total Counter :	1000640	Total Running Time :	1531 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.99	kN	No		
HEP :	25.0 %	11.53	kN	Yes 10	Rotations 15	Tablets
HCP :	5.0 %	9.68	kN	Yes 15	Times	
Ref :		9.22	kN			
LCP :	5.0 %	8.76	kN	Yes 15	Times	
LEP :	25.0 %	6.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	6.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.78	kN	Min :	2.74	kN	Punch NO.;	34
SD :	0.60	%	Max :	2.83	kN	Punch NO.;	11
Mean Main Pressure :	9.12	kN	Min :	8.26	kN	Punch NO.;	47
SD :	4.10	%	Max :	9.92	kN	Punch NO.;	51
Filling Depth :	Increase ; 549	Times	Decrease ;	543	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	26	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.64	mm	Main Thickness ;	2.65	mm
Filling Depth :	7.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.765	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.10	kN	Max Punch ;	35
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	17
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	1000640	Tablets			
A.W.C Counter :	991688	Tablets			
HEP :	1392 (0.1%)	Tablets	LEP :	949 (0.1%)	Tablets
GOOD :	989347 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	rp98927	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	05 Hour 37 Min 11 Sec
Total Counter :	1000640	Total Running Time :	1531 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	86	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	12.33	kN	No		
HEP :	24.0 %	11.76	kN	Yes	10	Rotations 15 Tablets
HCP :	5.0 %	9.96	kN	Yes	15	Times
Ref :		9.48	kN			
LCP :	5.0 %	9.01	kN	Yes	15	Times
LEP :	24.0 %	7.21	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.64	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.51	kN	Min :	2.47	kN	Punch NO.;	30
SD :	0.90	%	Max :	2.56	kN	Punch NO.;	11
Mean Main Pressure :	9.14	kN	Min :	8.05	kN	Punch NO.;	30
SD :	6.00	%	Max :	10.61	kN	Punch NO.;	13
Filling Depth :	Increase ;	430	Times	Decrease ;	438	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	24	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.30	mm	Current Cam :	Cam C	
Main Air pressure :	0.765	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.12	kN	Max Punch ;	35
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.15	kN	Max Punch ;	17
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	1000640	Tablets			
A.W.C Counter :	991688	Tablets			
HEP :	1392 (0.1%)	Tablets	LEP :	949 (0.1%)	Tablets
GOOD :	989347 (99.8%)	Tablets			