

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	16 Hour 00 Min 20 Sec
Total Counter :	2851466	Total Running Time :	1542 Hour 6 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	11.94	kN	No		
HEP :	25.0 %	11.49	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	9.37	kN	Yes	15	Times
Ref :		9.19	kN			
LCP :	2.0 %	9.00	kN	Yes	15	Times
LEP :	25.0 %	6.89	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	6.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.77	kN	Punch NO.;	18
SD :	0.60	%	Max :	2.86	kN	Punch NO.;	11
Mean Main Pressure :	9.14	kN	Min :	8.36	kN	Punch NO.;	27
SD :	4.10	%	Max :	10.10	kN	Punch NO.;	13
Filling Depth :	Increase ;	881	Times	Decrease ;	929	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.67	mm	Main Thickness ;	2.68	mm
Filling Depth :	7.15	mm	Current Cam :	Cam C	
Main Air pressure :	0.800	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.14	kN	Max Punch ;	35
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	16
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	19

Tablet Data (N/A)

Total Counter :	2851466	Tablets			
A.W.C Counter :	2838568	Tablets			
HEP :	2704 (0.1%)	Tablets	LEP :	2232 (0.1%)	Tablets
GOOD :	2833632 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MET 500 MG,STEW1A00
User ID :	pb97604	Batch NO. :	EWM2511950
Print Interval :	50000 Tablets	Running Time :	16 Hour 00 Min 20 Sec
Total Counter :	2851466	Total Running Time :	1542 Hour 6 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		4500000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	13.08	kN	No		
HEP :	24.0 %	12.48	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	10.27	kN	Yes	15	Times
Ref :		10.06	kN			
LCP :	2.0 %	9.86	kN	Yes	15	Times
LEP :	24.0 %	7.65	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	7.05	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.55	kN	Punch NO.;	33
SD :	1.00	%	Max :	2.68	kN	Punch NO.;	13
Mean Main Pressure :	10.42	kN	Min :	8.75	kN	Punch NO.;	34
SD :	6.70	%	Max :	12.24	kN	Punch NO.;	6
Filling Depth :	Increase ;	926	Times	Decrease ;	849	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.01	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.60	mm	Main Thickness ;	2.61	mm
Filling Depth :	7.33	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	31	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.14	kN	Max Punch ;	35
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	16
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.13	kN	Max Punch ;	52

Tablet Data (N/A)

Total Counter :	2851466	Tablets			
A.W.C Counter :	2838568	Tablets			
HEP :	2704 (0.1%)	Tablets	LEP :	2232 (0.1%)	Tablets
GOOD :	2833632 (99.8%)	Tablets			