

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	ks99394	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 34 Min 48 Sec
Total Counter :	85672	Total Running Time :	1551 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	54	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	8.33	kN	No		
HEP :	25.0 %	8.01	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	6.54	kN	Yes 15	Times	
Ref :		6.41	kN			
LCP :	2.0 %	6.28	kN	Yes 15	Times	
LEP :	25.0 %	4.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.49	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.56	kN	Punch NO.;	17
SD :	0.60	%	Max :	2.63	kN	Punch NO.;	36
Mean Main Pressure :	6.57	kN	Min :	5.82	kN	Punch NO.;	18
SD :	5.30	%	Max :	7.21	kN	Punch NO.;	35
Filling Depth :	Increase ; 4	Times	Decrease ; 7	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	1.71	mm
Filling Depth :	5.48	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.46	kN		
	Max ;	0.66	kN	Max Punch ;	66
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	3
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	85672	Tablets			
A.W.C Counter :	67110	Tablets			
HEP :	316 (0.5%)	Tablets	LEP :	60 (0.1%)	Tablets
GOOD :	66734 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	ks99394	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	00 Hour 34 Min 48 Sec
Total Counter :	85672	Total Running Time :	1551 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		70	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	8.31	kN	No		
HEP :	24.0 %	7.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	6.52	kN	Yes 15	Times	
Ref :		6.40	kN			
LCP :	2.0 %	6.27	kN	Yes 15	Times	
LEP :	24.0 %	4.86	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	4.48	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.37	kN	Min :	2.34	kN	Punch NO.;	58
SD :	0.70	%	Max :	2.44	kN	Punch NO.;	76
Mean Main Pressure :	5.48	kN	Min :	4.86	kN	Punch NO.;	10
SD :	7.40	%	Max :	7.26	kN	Punch NO.;	76
Filling Depth :	Increase ;	17	Times	Decrease ;	16	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.72	mm	Main Thickness ;	1.73	mm
Filling Depth :	5.98	mm	Current Cam :	Cam B	
Main Air pressure :	0.809	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	44	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.46	kN		
	Max ;	0.66	kN	Max Punch ;	66
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	3
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.06	kN	Max Punch ;	77

Tablet Data (N/A)

Total Counter :	85672	Tablets			
A.W.C Counter :	67110	Tablets			
HEP :	316 (0.5%)	Tablets	LEP :	60 (0.1%)	Tablets
GOOD :	66734 (99.4%)	Tablets			