

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A00
User ID :	sj97904	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 38 Sec
Total Counter :	237142	Total Running Time :	1552 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	35	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	10.07	kN	No		
HEP :	25.0 %	9.69	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	7.90	kN	Yes 15	Times	
Ref :		7.75	kN			
LCP :	2.0 %	7.59	kN	Yes 15	Times	
LEP :	25.0 %	5.81	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	5.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.60	kN	Min :	2.56	kN	Punch NO.;	68
SD :	0.50	%	Max :	2.63	kN	Punch NO.;	35
Mean Main Pressure :	7.75	kN	Min :	7.32	kN	Punch NO.;	19
SD :	3.10	%	Max :	8.68	kN	Punch NO.;	35
Filling Depth :	Increase ; 66	Times	Decrease ;	46	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	6.02	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	112	Min			
Lower Punch Remain Time (S2):	86	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.98	kN		
	Max ;	1.17	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	3
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	237142	Tablets			
A.W.C Counter :	205382	Tablets			
HEP :	999 (0.5%)	Tablets	LEP :	173 (0.1%)	Tablets
GOOD :	204210 (99.4%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SERTRA50MG,STJL1A0
User ID :	sj97904	Batch NO. :	JLM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 07 Min 38 Sec
Total Counter :	237142	Total Running Time :	1552 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	30	%	Manual ;	16	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		700000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		150	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		150	Min	Supply Time ;	0.2	Sec
Powder Supply Time :		30.0	Sec			
Initial Reject Time :		1	Tablets			
Upper Punch Tightness High Limit :		2.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	9.77	kN	No		
HEP :	24.0 %	9.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	7.67	kN	Yes	15	Times
Ref :		7.52	kN			
LCP :	2.0 %	7.36	kN	Yes	15	Times
LEP :	24.0 %	5.71	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	5.26	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.39	kN	Min :	2.36	kN	Punch NO.;	68
SD :	0.60	%	Max :	2.44	kN	Punch NO.;	36
Mean Main Pressure :	7.53	kN	Min :	6.88	kN	Punch NO.;	16
SD :	4.80	%	Max :	8.95	kN	Punch NO.;	35
Filling Depth :	Increase ;	98	Times	Decrease ;	94	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	30	RPM	Capacity :	277200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.49	mm	Pre Thickness ;	3.50	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.75	mm	Main Thickness ;	1.76	mm
Filling Depth :	6.19	mm	Current Cam :	Cam B	
Main Air pressure :	0.807	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	112	Min			
Lower Punch Remain Time (S2):	86	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.98	kN		
	Max ;	1.17	kN	Max Punch ;	32
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	3
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	237142	Tablets			
A.W.C Counter :	205382	Tablets			
HEP :	999 (0.5%)	Tablets	LEP :	173 (0.1%)	Tablets
GOOD :	204210 (99.4%)	Tablets			